

Philips LED
Reflector

3 W (20 W)
GU4
Warm white
Non-dimmable

8718696708668



Light that's easy on your eyes

Comfortable light from the world leader in lighting

Poor quality light could cause eye strain. It's more important than ever to properly light your home. Philips LED lamps fulfil stringent test criteria to ensure that they meet our Eyecomfort requirements†

Choose for the high-quality light
- Learn about light

Choose a simple replacement for your old lamps
- No UV or InfraRed

Choose for a sustainable solution
- Long-life bulbs – Last up to 15 years

Create the right light for your home
- Perfect for accent lighting

Comfortable LED light that is easy on your eyes
- Designed for the comfort of your eyes
- No visible flicker

PHILIPS

Reflector
3 W (20 W) GU4, Warm white, Non-dimmable

8718696708668

Highlights

15,000-hour rated average life



With a lifetime of up to 15,000 hours, you can reduce the hassle of frequently replacing your light bulbs, and enjoy a perfect lighting solution for over 15 years.

Perfect for accent lighting



Modern lighting with a familiar wide-angle light output (36 degrees), this LED spot is suitable for both accent lighting and general-purpose lighting. It can be used in recesses and track light fixtures, and is ideal for use in kitchens, kitchen island lighting, living rooms and dining rooms.

No UV or IR



The light has no infra-red component, so no heat is radiated. Also, there is no ultra-violet component in this light. These two characteristics mean that this light will not cause fabric and other items to fade.

Learn about light



Colour temperature: light can have different colour temperatures, indicated in units called Kelvin (K). Bulbs with a low Kelvin value produce a warm, more tranquil light, while those with a higher Kelvin value produce a cool, more energising light. CRI: the colour rendering index (CRI) is used to describe the effect of a light source on colour appearance. Natural sunlight has a CRI of 100. The CRI of Philips LED light bulbs is always higher than 80, which ensures that colours are shown as true and natural.

Gentle LEDs, easy on the eyes



It's easy to see how harsh lighting can strain the eyes. Too bright, and you get glare. Too soft and you experience flicker. Now you can gently light up your world with LEDs designed to go easy on the eyes, and create the perfect ambience for your home.

No visible flicker

When your light flickers in quick succession it could be hard on the eyes, cause headaches and even set off an attack for those with photosensitive epilepsy. It's both unpleasant and unnecessary. LEDs can flicker because of their rapid response to the driver current. However, because Philips LEDs are designed so that variations in your driver current's output are minimised, they eliminate the factors that cause flicker. So, you won't see it, not even a hint.

Specifications

Bulb characteristics
- Shape: Spot
- Cap/fitting: GU4
- Dimmable: No
- Voltage: 12 V
- Wattage: 3
- Wattage equivalent: 20

Power consumption
- Energy efficiency label: A+
- Power consumption per 1000h: 3 kW·h

Light characteristics
- Light output: 190 lumen
- Beam angle: 36 degree
- Colour: Warm White
- Colour temperature: 2700 K
- Colour rendering index (CRI): 80
- Starting time: <0.5 s
- Warm-up time to 60% light: Instant full light
- EyeComfort: Eye Comfort

Durability
- Lifetime of lamp: 15000 hour(s)
- Number of switch cycles: 50000
- Lumen maintenance factor: 0.7
- Average life (at 2.7 hrs/day): 15 year(s)

Bulb dimensions
- Height: 37.5 mm
- Width: 35 mm

Other characteristics
- Mercury content: 0 mg
- Lamp current: 350 mA
- Lamp Classification Risk Group: RG1

Issue date 2018-11-09

Version: 4.0.1

12 NC: 9290 013 39201
EAN: 87 18696 70866 8

© 2018 Philips Lighting Holding B.V.
All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Philips Lighting Holding B.V. or their respective owners.

www.philips.com

* Designed for the comfort of your eyes. Visit www.philips.com/eyecomfort for flicker, strobe and other criteria and product details.
* PstLM is smaller or equal to 1.0, measured according to IEC 61547-1 and IEC 61000-4-15.