Philips LED
Candle

4.3 W (40 W)
E14
Warm white
Non-dimmable

8718696751275





Designed to be seen

Looks good off and on

Familiar shapes that you know and love. They use around 80% less energy than traditional light bulbs thanks to the latest LED energy-saving technology and last ten times longer. With EyeComfort†, for light that's easy on your eyes.

Choose for the high-quality light
- True incandescent-like warm white light
- Learn about light

Light beyond illumination
- Vintage style, modern LED technology
- A simple LED for everyday use

Choose a simple replacement for your old bulbs
- Similar shape and size as incandescent lustres
- Instant light when switched on
- No UV or InfraRed

Choose for a sustainable solution
- Long-life bulbs – Last up to 15 years
- Better for your wallet and your planet

PHILIPS

Candle
4.3 W (40 W) E14, Warm white, Non-dimmable

8718696751275

Highlights

Incandescent-like warm white



This bulb has a colour temperature of 2,700 K, providing you with a warm, tranquil atmosphere, perfect for relaxing. This 2,700 K light is ideal for home lighting design

Vintage-style, modern LED

LED Classic bulbs are based on standard LED energy-saving technology. Now you can enjoy a retro-style bulb with state-of-the-art technology combined with vintage design.

A simple LED for everyday use



The Philips everyday LED is the perfect lamp for your basic lighting needs. It provides the beautiful light and dependable performance that you expect from LED at an affordable price.

Replaces lustre incandescents



With its beautifully shaped design and familiar dimensions, this is a contemporary lighting, LED lustre. The perfect sustainable replacement for traditional incandescent lustres.

Instant On



No need to wait: Philips LED light bulbs provide their full level of brightness immediately, as soon as they are switched on. Just by turning the switch, your room is at full brightness. There is no slow starting or waiting.

15,000-hour rated average life



With a lifetime of up to 15,000 hours, you can reduce the hassle of frequently replacing your light bulbs, and enjoy a perfect lighting solution for over 15 years.

Saves up to 80% energy



LED technology saves up to 80% energy compared to your standard bulb. It therefore pays for itself and saves you money year after year. It also helps to protect the environment.

No UV or IR



The light has no infra-red component, so no heat is radiated. Also, there is no ultra-violet component in this light. These two characteristics mean that this light will not cause fabric and other items to fade.

Candle
4.3 W (40 W) E14, Warm white, Non-dimmable

8718696751275

Specifications

Bulb characteristics
- Shape: Lustre
- Cap/fitting: E14
- Dimmable: No
- Voltage: 220–240 V
- Wattage: 4.3
- Wattage equivalent: 40

Power consumption
- Energy efficiency label: A++
- Power consumption per 1000h: 5 kW·h

Light characteristics
- Light output: 470 lumen
- Colour: Warm White
- Colour temperature: 2700 K
- Light effect/finish: Warm White
- Colour rendering index (CRI): 80
- Starting time: 0.5 s
- Warm-up time to 60% light: Instant full light
- EyeComfort: Eye Comfort

Durability
- Lifetime of lamp: 15000 hour(s)
- Number of switch cycles: 20000
- Lumen maintenance factor: 0.7
- Average life (at 2.7 hrs/day): 15 year(s)

Bulb dimensions
- Height: 82 mm
- Width: 45 mm

Other characteristics
- Mercury content: 0 mg
- Power factor: 0.4
- Lamp current: 40 mA
- Range: LED Classic

Rated values
- Rated power: 4.3 W
- Rated luminous flux: 470 lumen
- Rated lifetime: 15000 hour(s)

Issue date 2018-11-09

Version: 3.0.1

12 NC: 9290 012 58171
EAN: 87 18696 75127 5

© 2018 Philips Lighting Holding B.V.
All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Philips Lighting Holding B.V. or their respective owners.

www.philips.com

* Designed for the comfort of your eyes. Visit www.philips.com/eyecomfort for flicker, strobe and other criteria and product details.
* PstLM is smaller or equal to 1.0, measured according to IEC 61547-1 and IEC 61000-4-15.