MPN: FIB211005

Optical Fibre Cable, MTRJ-ST, Multimode, Duplex, OM3 (Aqua Blue), 5m

The 50/125µm OM3 multimode bend insensitive fiber optic cable is less attenuation when bent or twisted compared with traditional optical fiber cables and this will make the installation and maintenance of the fiber optic cables more efficient. This 50/125 OM3 multimode fiber optic cable is ideal for connecting 10G SR, 10G LRM, SFP+ transceivers etc. for 10G/40G/100G Ethernet connections and is the preferred fiber specification for 10G Ethernet connections. The multimode patch cords are manufactured using LSZH cables which conform to IEC, EIA TIA or Telcordia standards.

- Designed for Data Centers, Industry and Computer Centers
- LSZH (Low Smoke Zero Halogen) and flame retardant
- RoHS compliant
- Fibre Standard G.652.D

Specifications

Features	**Cable length**	5 m
	Cladding diameter	125 µm
	Connector 1	ST/UPC
	Connector 1 gender	Male
	Connector 2	MTRJ/UPC
	Connector 2 gender	Male
	Core diameter	50 µm
	Fiber mode structure	Multi-mode
	Fibre optic type	OM3
	Halogen-free	Yes
	InfiniBand protocol	Yes
	Insertion loss	0.3 dB
	Jacket material	Low smoke zero halogen (LSZH)
	Product colour	Aqua colour
	RoHS compliance	Yes
Legal Information	**ADR Information**	No restrictions
	Country of Origin	China
	EU ECCN Code	N/A
	Tariff No.	8544700099
	UNSPSC Code	26121607
	US ECCN Code	EAR99
Operational conditions	**Operating temperature (T-T)**	-40 - 85 °C
	Storage temperature (T-T)	-40 - 85 °C
Other features	**Core / cladding diameter**	50/125 µm

Package dimensions	**Gross Weight (Package, kg)**	0.07 kg
Product dimensions	**Net Weight (Product, kg)**	0.06 kg
Vendor information	**Brand Name**	MicroConnect
	Homepage	https://microconnect.me/
	Warranty	25 Year(s)
Weight & dimensions	**Cable diameter**	2 mm