

PacificLED gen4

WT470X LED35S/840 VWB ACW TC5 L1600

PACIFIC LED GREEN PARKING - 840 neutral white - Very wide beam - Screw connection with pug and socket

PacificLED gen4 is a highly efficient and reliable LED waterproof luminaire that offers an excellent quality of light, with a uniform light distribution without visible striping or color artefacts. The range offers modular construction to enable ease of upgrade and maintenance.The new optical system provides distortion-free lighting with improved visual guidance, which makes it ideally suited to general industry, warehouses and parking areas. The range also offers the option of multiple optics to ensure an optimized lighting scheme for a wide range of applications.For industrial applications, PacificLED gen4 offers an open product architecture with toolless access to the gear tray and an innovative end-cap design with built-in connector for fast and easy installation. The single-piece mounting clamp ensures no small, loose components which could affect the primary production process.

Product data

General Information	
Beam angle of light source	120 °
Light source colour	840 neutral white
Light source replaceable	Yes
Number of gear units	1 unit
Driver/power unit/transformer	PSD [Power supply unit with DALI interface]
Driver included	Yes
Optic type	VWB [Very wide beam]
Luminaire light beam spread	120° x 120°
Control interface	DALI
Connection	SI-PS [Screw connection with pug and socket]
Cable	-

Protection class IEC	Safety class I (I)
Glow-wire test	850/5 [Temperature 850 °C, duration 5 s]
Flammability mark	D [For mounting on easily flammable surfaces]
CE mark	CE mark
ENEC mark	ENEC mark
Warranty period	5 years
Constant light output	No
Number of products on MCB	24
RoHS mark	RoHS mark
Product Family Code	WT470X [PACIFIC LED GREEN PARKING]

PacificLED gen4

Operating and Electrical	
Input voltage	220-240 V
Input frequency	50 to 60 Hz
Inrush current	21 A
Inrush time	0.28 ms
Power factor (min.)	0.96

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Housing material	Polycarbonate
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Optical cover/lens finish	Clear
Overall length	1621 mm
Overall width	96 mm
Overall height	108 mm

Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]

Initial Performance (IEC Compliant)	
Initial luminous flux	3536 lm
Luminous flux tolerance	+/-7%
Initial LED luminaire efficacy	145 lm/W
Init. Corr. colour temperature	4000 K
Init. colour rendering index	>80
Initial chromaticity	(0.38, 0.38) SDCM <3
Initial input power	24.4 W
Power consumption tolerance	+/-11%

Over Time Performance (IEC Compliant)	
Driver failure rate at 5,000 hours	0.5 %
Median useful life L70B50	70000 h
Median useful life L80B50	50000 h
Median useful life L90B50	25000 h

Application Conditions	
Ambient temperature range	-25 to +45 °C
Maximum dimming level	1%
Suitable for random switching	Not applicable

Product Data	
Full product code	871869638026000
Order product name	WT470X LED35S/840 VWB ACW TC5 L1600
EAN/UPC – product	8718696380260
Order code	38026000
Numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12NC)	910925863905
Net weight (piece)	3.460 kg



Dimensional drawing



Pacific LED Green Parking WT470X-WT485X

PacificLED gen4

Photometric data





IFGU1_WT470XL16001xLED35S840VWB

IFPC1_WT470XL16001xLED35S840VWB

© 2017 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.