WHI643ORAB

Freestanding wall decorative cooker hood



- P.A.S. System
- AdaptTech
- Timer and refresh
- LedLight

Freestanding wall cooker hood
Venting with air extraction or recirculation
Energy class: **B**
Material of housing/chimney: **varnished steel**

Lightning efficiency class: **B**
Grease filtering efficiency class: **A**
Fluid dynamic efficiency class: **B**
Maximum extraction rate by extraction operation: **570 m³/h**
Venting tube diameter: **15 cm**

Air flow by extraction version, step 1: **342 m³/h**
Air flow by extraction version, step 3: **570 m³/h**

AdaptTech: Automatic fan operation
Electronic control
Control setting: **Touch control**
Timer function
Number of speed positions: **3**

Constant ventilation ReFresh
Lamp type: **LED**
Dimmer function
Number of lights: **2**
Power of lights: **8 W**
Airflow boost position (PowerBoost 2) - extraction: **740 m³/h**
Perimetric suction

Filter material: **Washable aluminium with polyurethane foam**
Grease filter indicator
Motor type: **Capacitor motor**
Number of motors: **1**
Number of PowerBoost functions: **2**
No return airflow flap: **150 mm**

Max. noise level: **59 dB(A)re 1 pW**
Height: **425 mm**
Min. height of the chimney: **420 mm**
Max. height of the chimney: **620 mm**
Annual energy consumption : **60.6 kWh**
Dimensions (W×H×D): **60 × 42.5 × 47 cm**
Dimensions of packed product (W×H×D): **70.5 × 52 × 56.2 cm**
Net weight: **26 kg**
Gross weight: **30 kg**
Connection rating: **284 W**
Nominal current of fuse: **10 amp**
Code: **728153**
EAN code: **3838782027437**

http://www.gorenje.cn/en/product/728153