Philips
DVI cable

1.5 m

SWV5565





Create a superior viewing experience

with this video cable

Experience a new level of viewing while transferring video signals between your components. Superior construction delivers improved picture performance.

Enjoy better picture quality
- 24 carat gold-plated connectors optimise signal
- Stranded conductor extends durability
- High-bandwidth Digital Content Protection

Protects against signal loss
- 100% aluminium shielding
- Oxygen-free copper conductor for ideal signal transfer
- Copper-braided reinforced aluminium shielding

Easy installation
- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability
- Protective metal shell for extended durability
- Super pliable jackets for outstanding flexibility
- Rubber strain relief

PHILIPS
sense and simplicity

DVI cable
1.5 m

SWV5565/10

Specifications

Packaging Data
- Quantity: 1
- EAN/UPC/GTIN: 87 10895 93455 8
- Gross weight: 0.74 kg
- Tare weight: 0.13 kg
- Net weight: 0.61 kg
- Length: 265 mm
- Width: 195 mm
- Height: 100 mm

Inner Box
- EAN/UPC/GTIN: 87 10895 97054 9
- Quantity: 2
- Gross weight: 1.82 kg
- Tare weight: 0.6 kg
- Net weight: 1.22 kg
- Length: 280 mm
- Width: 175 mm
- Height: 210 mm

Outer Box
- EAN/UPC/GTIN: 87 10895 97055 6
- Quantity: 4
- Gross weight: 4.31 kg
- Tare weight: 1.87 kg
- Net weight: 2.44 kg
- Length: 370 mm
- Width: 300 mm
- Height: 230 mm

Product highlights

24 carat gold-plated connector
24 carat gold-plated connectors ensure the best signal quality for your components.

Stranded conductor
The stranded wire evenly distributes stress so no single area is overburdened. It provides more flexibility for easier positioning.

HDCP Compliant
High-bandwidth Digital Content Protection (HDCP) allows you to play protected content media such as movies and concerts. It checks the signal to prevent piracy, allowing only legal copies of content to display.

100% aluminium shielding
This protective layer of aluminium guards against electromagnetic interference for improved signal quality.

Twisted high-purity OFC
This oxygen-free copper conductor provides the highest accuracy in signal transfer with minimal resistance.

Braided shielding
Copper-braided reinforced aluminium shielding protects against signal loss and interference.

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play
Plug and play offers easy installation of components without time-consuming installations.

Metal shell
The metal shell protects the internal connection of the cable. It ensures durability and reliability of your connection.

Super pliable jackets
Super pliable PVC jackets are abrasion-resistant for outstanding flexibility and protection against everyday wear and tear.

Rubber strain relief
Rubber strain relief provides a secure yet flexible juncture between the cable and the plug.

Issue date 2008-12-17
Version: 2.0.5
12 NC: 9082 100 06365
EAN: 87 10895 93462 6

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com