HYPERTEC
MAKING IT PERFORM

FR DE

ProDockLite

USB 3.1 Type-C Mini Dock

Universal USB-C

USB 3.1 Power Delivery

12 Month Warranty



Connect USB-C Laptops, Ultrabooks & Devices to Displays, Projectors, Networks, and other peripherals with ease!

Connectivity:

- ✓ Universal USB Type-C Connection
- ✓ USB 3.1 Type-C Port for Charging
- ✓ 2 x USB 3.0 Ports
- ✓ RJ45 Gigabit Ethernet Port
- ✓ 1080p VGA Support
- ✓ HDMI Supports 4K Ultra-HD Video
- ✓ SD Card Reader (Also reads MicroSD)
- ✓ 3.5mm Audio Output

Turn your USB-C Laptop into the Ultimate Hub

The new ProDockLite Mini Dock from Hypertec enables mobile workers with USB-C Laptops or Ultrabooks to connect to a variety of peripherals in the office or at home. Taking full advantage of the latest USB 3.1 Specification, the ProDockLite is capable of delivering high quality video, fast file transfer speeds and power delivery from a single Type-C connection.

Empower your workflow, wherever you are

The ProDockLite also features a USB 3.1 Type-C female port that allows users to charge their USB-C Laptop or Ultrabook while connected. With an ultra-portable design, the ProDockLite is ideal for Hot Desk applications and mobile work environments.

For more information on the **ProDockLite**, speak to your Hypertec Account Manager today.





Compatibility Tested with:

- ✓ ASUS ZenBook3U
- ✓ DELL Alienware
- ✓ DELL XPS 13
- ✓ HP EliteBook
- ✓ HP Spectre 13
- ✓ HUWAEI MateBook
- ✓ Lenovo Air12
- ✓ Lenovo Yoga
- ✓ Macbook 2015 / 2016
- ✓ Macbook Pro 13 / 15
- ✓ Google Pixel
- ✓ Microsoft Lumia 950
- ✓ HTC 10
- ✓ LG G5

Part Code:
HYP-USBCPD-L

Unit Length:
220mm
Net Weight:
168g

CE compliant. RoHS & REACH compliant.

Additional Technical Information

USB
USB Type-C female supports 20V 3A power charging for the dock and your USB-C PC.
2x USB 3.0 ports support up to 5Gbps data transfer and other standard USB devices (keyboards/mice/USB flash/hard disks, etc).
Support power outputs up to 900mA from USB ports.

Audio & Video
HDMI port supports up to max video resolution up to 4K*2K@30Hz. Both video & audio support.
VGA port supports up to max video resolution up to 1920*1080p@60Hz. It can support sound output by plugging a 3.5mm audio cable at the back side of the dock.
This dock does not support simultaneous VGA and HDMI display output.

Network & Other
Lan supports gigabit ethernet and does not require CD driver when you set up (disc free).
SD card reader supports SD card and micro SD card (TF card). Maximum read and write is 60Mbps/s in theory.

For more information on the **ProDockLite**, speak to a Hypertec Account Manager today.