AG neovo

THE DISPLAY CHOICE
OF PROFESSIONALS™

U-17



AG Neovo's most eco-minded display with unmatched durability and power efficiency in a stylish design ideal for the busiest multi-user environments.

With a bright 17-inch screen, stereo speakers, side-mount headphone jack and USB port, the U-17's multimedia feature set is matched only by its breakthrough power-saving technology. Fitted with durable touch-sensor controls and best-in-class NeoV™ Optical Glass, the U-17 easily becomes the smartest, most eco-friendly choice of professionals.

> LED backlight for energy saving and environmental consciousness
> NeoV™ Optical Glass
> Contemporary & professional design
> 1280 x 1024 resolution, 1000:1 contrast ratio and 3ms response
> Eco-friendly: Halogen-free, recyclable materials and green design
> Energy efficient: Zero-watt consumption with EcoSwitch
> Built-in headphone jack and stereo speakers
> Wear-resistant touch sensor controls
> Easy-access USB port (pass through)
> New intuitive OSD with settings lock
> Dual PC inputs: VGA and DVI
> Kensington® security socket
> VESA standard wall mount

NeoV OPTICAL GLASS

NeoV™ Optical Glass - The most trusted hard glass protection available. Only on AG Neovo displays

U-17

Specifications		U-17
Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	17.0” (432 mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.264 mm
	Brightness	250 cd/m²
	Contrast Ratio	1000:1
	Viewing Angle (H/V)	170°/160°
	Display Colour	16.7M
	Response Time	3 ms
Frequency (H/V)		H: 24 kHz - 81 kHz V: 56 Hz - 75 Hz
Input	Analogue	15-Pin D-Sub
	Digital	24-Pin DVI-D
Audio	Audio In	3.5 mm Audio Line-in
	Audio Out	3.5 mm Headphone Jack
	Speaker	1W x 2
Power	Power Supply	Internal
	Power Requirements	AC 100 - 240 V, 50 - 60 Hz
	Consumption	< 17 W (On) < 0.5 W (Stand-by) < 0.5 W (Off) = 0 W (EcoSwitch off)
NeoV™ Optical Glass	Thickness	3.0 mm (0.12”)
	Reflection Rate	< 1%
	Transmission Rate	> 96%
	Coating Hardness	> 9H
Plug & Play	VESA	DCC 2B, DDC/CI
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 90%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	5% ~ 95%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Tilt	Tilt	0° ~ +20°
Dimensions	Product (W x H x D)	397 x 390 x 174 mm (15.6” x 15.4” x 6.9”)
	Packaging (W x H x D)	488 x 480 x 143 mm (19.2” x 18.9” x 5.6”)
Weight	Product	4.9 kg (10.8 lbs)
	Packaged	6.9 kg (15.2 lbs)
Regulation Approval	Certifications & Compliance	CB, FCC, CE, GOST-R, WEEE, Energy Star, RoHS, REACH, BSMI
Accessories	Supplied	CD ROM (user manual), audio cable, AC power cord and 15-Pin D-Sub cable



Side-mount headphone jack, USB port and built- in stereo speakers for multimedia convenience



Durable, long-lasting touch sensor controls won’t wear out like mechanical buttons



NeoV™ Optical Glass protects against scratches, impacts and other physical damage



Slash power bills and CO_2 emissions by up to 50% (67% versus CRTs); EcoSwitch cuts power usage to zero when off

ENERGY STAR REACH RoHS COMPLIANT WEEE

All specifications are subject to change without prior notice.
Copyright © 2016 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC.
All other trademarks are the property of their respective owners.
P/C: U170D0 Version 8.0, 20160531