49" Ultra-Narrow Bezel Commercial Display

CDX4952



With stunning brightness, vibrant images, and multi-screen tiling, the ViewSonic® CDX4952 49" (48.5" viewable) commercial display is your ideal tool for creating video walls that wow! With up to 10x10 tiling installation, and an ultra-narrow bezel that measures only 3.5mm between combined displays, the CDX4952 delivers nearly seamless, high-impact messaging that helps you to astonish, inspire, and inform. Featuring full metal construction and a scratch-resistant tempered glass screen, this durable commercial-grade display delivers reliable messaging 24 hours a day, 7 days a week. With Full HD 1080p resolution, 450-nit brightness, SuperClear® technology for wide viewing angles, and dual 10W stereo speakers, the CDX4952 delivers sharp, vivid images with incredible sound for superior multimedia performance.

Key Features:
Ultra-narrow Bezel
10x10 Tiling Support with DisplayPort or DVI
Control Multiple Devices
Free Bundled vController Software
OPS PC Slot

Designed for:
Video Wall Applications

49" Ultra-Narrow Bezel Commercial Display

CDX4952

Specifications

LCD PANEL	Panel Size	49" (48.5" diagonal)
	Type/ Tech	TFT LCD Module. (IPS type, DLED backlight)
	Display Area (mm)	1073.8(H) x 604.0 (V) (48.50" diagonal)
	Aspect Ratio	16:9
	Resolution	1920 x 1080
	Colors	10 bit, 1.07 Billion colors
	Brightness	450 nits (typ.)
	Contrast Ratio	1300:1 (typ.)
	Response Time	12 ms
	Viewing Angles	H = 178°, V = 178° (typ.)
	Backlight	LED
	Backlight Life	50,000 Hours (typ.)
	Hardness	Hard coating(3H), Anti-glare treatment of the front polarizer, Haze 1%(Typ.)
INPUT	HDMI	x 2 (1.4)
	RGB / VGA	x1
	DisplayPort	x1
	DVI	x1
	Audio	x1
	CVBS	x 1 (Share with component Y)
	YPbPr	x1
	RS232	x1
	OPS	x1
	IR Pass Through	x1
OUTPUT	DisplayPort	x1
	DVI	x1
	Audio	x1
	RS232	x1
	IR Pass Through	x1
LAN	RJ45	x1
SPEAKERS		10W x2
COMPATIBILITY	CVBS	480i
	HDMI (1080p)	480i, 480p,720p,1080i,1080p, 4k2k@30Hz
	DisplayPort	480i, 480p,720p,1080i,1080p, 4k2k@30Hz
	YPbPr	480i, 480p,720p,1080i,1080p
	DVI	480i, 480p,720p,1080i,1080p
POWER	Voltage	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
	Consumption	Normal 110 W, Max 235 W
ERGONOMICS	Wall Mount (VESA)	400x400mm ; Screw: M6*10mm
OPERATING CONDITIONS	Temperature (° C)	5 – 40 degC (Landscape), 5 – 35 degC (Portrait)
	Humidity	20% ~ 80% without condensation
DIMENSIONS (W x H x D)	Physical (inch / mm)	1077.6 x 648.7 x 400 mm / 42.43' x 25.54' x 15.75' in.
	Physical w/o Stand (inch / mm)	1077.6 x 607.8 x 93.5 mm / 42.43 'x 23.93' x 3.68' in
	Packaging (inch / mm)	1367 x 897 x 366 mm / 53.82' x 35.31' x 14.41' in
WEIGHT	Net (lb / kg)	23.9 kg / 52.69 lb
REGULATIONS	Standard	UL/cUL, FCC, Energy Star 7.0, UL-MX-CoC, Mexico Energy
What's in the box?		CDX4952 Commercial Display / Remote Control with batteries / User manual CD wizard / Quick Start Guide / Power Cables / VGA cable / RS232 cable / IR sensor cable / RS232 daisy chain cable / Edge Alignment Kit-1 / Edge Alignment Kit-2 / Thumb Screw *Actual content may differ from market to market