ThinkSystem SR570 7Y03A027EA

Region
EET,MEA,RUCIS,WE

Machine Type
7Y03

TopSeller
TopSeller

Processor
1x Xeon Silver 4114
10C/2.2GHz/13.75MB/85W/DDR4-2400

Memory
1x 32GB RDIMM DDR4-2666

Storage Controller
1x 930-8i 2GB Flash

Disk Bays
8x 2.5" SATA/SAS HS

Disks
Open

M.2 Drives
None

Networking (LOM/ML2/PCIe)
None

Available PCIe Slots
1x PCIex8, 1x PCIex16

FrontVGAport
None

System Management
XClarity Advanced

Power Supply
2x 750W Platinum

Warranty
3-year

Ann Date (mm/yy)
11/17

Note:
Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX - Hungary, CY - Cyprus, etc.), and "**" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries

www.lenovo.com

This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area. Lenovo reserves the right to change specifcations or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication “as is” without warranty of any kind, either express or implied, including the implied warranties of merchantability or ftness for a particular purpose.

http://psref.lenovo.com
Visit psref website for the latest version of Product Specifcations Reference.

© Lenovo, 2017. All rights reserved.



ThinkSystem SR570 Platform Specifications

Components	Specification
Form factor	1U rack
Dimensions	Height: 43 mm (1.7 in). Width: 482 mm (19.0 in) with rack latches. Depth: 778.3 mm (30.64 in)
Weight	Maximum configuration: 35.27 lb (16 kg)
Processor	Up to two 150W Intel Xeon Scalable family processors, Bronze, Silver, Gold, or Platinum. Up to 26 cores at 2.0GHz, up to 3.6GHz with 4 cores. Two processors are connected with two UPI (Ultra Path Interconnect) links up to 10.4GT/s each
Chipset	Intel C622 Platform Controller Hub
Memory	Up to 16 DIMM sockets. Each processor supports up to 8 DIMM sockets with 6 channels. DDR4-2666. RDIMMs and LRDIMMs are supported, but memory types cannot be intermixed
Memory capacity	With RDIMMs: Up to 512GB with 16 x 32 GB RDIMMs and two processors With LRDIMMs: Up to 1TB with 16 x 64 GB LRDIMMs and two processors
Memory protection	ECC, memory mirroring, and memory sparing
Storage controllers	Supports the following RAID/HBA adapters:

	RAID adapter	Interface	Drive type	RAID levels	JBOD	Cache	Cache protection	FastPath	Max qty
For SS bays	Onboard SATA	6Gb SATA	SATA	0/1/10/5	Yes	None	None	No	-
For HS bays	530-8i	12Gbs SAS	SATA/SAS	0/1/10/5/50	Yes	None	None	Yes	1
	730-8i	12Gbs SAS	SATA/SAS	0/1/10/5/50	Yes	1GB	None	No	1
	930-8i	12Gbs SAS	SATA/SAS	0/1/10/5/50/6/60	Yes	2GB	Flash backup	Yes	1
	930-16i	12Gbs SAS	SATA/SAS	0/1/10/5/50/6/60	Yes	4GB	Flash backup	Yes	1
	430-8i	12Gbs SAS	SATA/SAS	-	Yes	None	None	-	1
	430-16i	12Gbs SAS	SATA/SAS	-	Yes	None	None	-	1
	430-8e	12Gbs SAS	SATA/SAS	-	Yes	None	None	-	3
	430-16e	12Gbs SAS	SATA/SAS	-	Yes	None	None	-	3
	930-8e	12Gbs SAS	SATA/SAS	0/1/10/5/50/6/60	Yes	4GB	Flash backup	Yes	2

Note: 730-8i is available in China only

Disk drive bays	Support 4 front 3.5" SATA simple-swap bays, or 4 front 3.5" SATA/SAS HS bays, or 8 front 2.5" SATA/SAS HS bays, or 10 front 2.5" SATA/SAS HS bays with 4 AnyBay. Optional one or two internal M.2 SSD for boot, dual M.2 SSD supports mirroring		
Internal storage	For 3.5" SS bay	3.5" HDD, SATA6Gbs, 7.2K	1TB/2TB/4TB/6TB/8TB
	For 3.5" bay (3.5" disks or 2.5" disks with 3.5" tray)	3.5" HDD, SATA6Gbs, 7.2K	1TB/2TB/4TB/6TB/8TB/10TB
		3.5" HDD, SAS12Gbs, 7.2K	1TB/2TB/4TB/6TB/10TB
		3.5" HDD, SAS12Gbs, 15K	300GB/600GB/900GB
		2.5" SSD, SATA6Gbs	240GB/480GB
		2.5" NVMe SSD, AnyBay	960GB/1.92TB/3.84TB
	For 2.5" bay	2.5" HDD, SATA6Gbs, 7.2K	1TB/2TB
		2.5" HDD, SAS12Gbs, 7.2K	1TB/2TB
		2.5" HDD, SAS12Gbs, 10K	300GB/600GB/900GB/1.2TB/1.8TB
		2.5" HDD, SAS12Gbs, 10K, SED	300GB/600GB
		2.5" HDD, SAS12Gbs, 15K	300GB/600GB/900GB
		2.5" SSD, SAS12Gbs	400GB/800GB/3.84TB
		2.5" SSD, SATA6Gbs	240GB/480GB
		2.5" NVMe SSD, AnyBay	960GB/1.6TB/1.92TB/3.84TB
	M.2 boot drive	M.2 SATA SSD	32GB/128GB
Optical	No internal optical bay. Optional USB DVD±RW optical drive		
Network interfaces	Integrated one dedicated management port plus two GbE ports. One LOM slot for customized LOM with two RJ-45 or SFP+ ports, up to 10GbE. Optional ML2 or PCIe adapters are supported. ML2 adapter requires riser card with ML2 slot. Up to two ports supports Wake-on-LAN and NC-SI (see right)		
Security features	Power-on and admin password. Trusted Platform Module, TCG 1.2 compliant, upgrade to 2.0 via UEFI setting. Optional TCM in China only. Optional lockable security bezel		
Operating systems supported	Microsoft Windows Server 2016/2012 R2. Red Hat Enterprise Linux 7.3/6.9. SUSE Linux Enterprise Server 12 SP2/11 SP4. VMware ESXi 6.5/6.0 U3		
Systems management	XClarity Controller Standard, optional upgrades to Advanced or Enterprise are available. Energy Manager. XClarity Administrator. Lenovo Capacity Planner. Provisioning Manager. Essentials. Light Path Diagnostics		
GPU support	None		

Components	Specification
Base warranty	MT 7Y02: 1-year limited onsite service with 9x5/NBD MT 7Y03: 3-year limited onsite service with 9x5/NBD
Power supply	Up to two redundant hot-swap 550W and 750W 80 PLUS Platinum qualified AC power supplies. Or up to two redundant hot-swap 750W Titanium qualified AC power supplies. 750W Titanium is 200V - 240V, others are 100V - 240V
Video	Integrated Matrox G200 in XClarity Controller
Cooling	4x 3.5" or 8x 2.5" models: four fans for single processor model, six fans for dual processor model, all fans are 4028 10x 2.5" models: six fans for both single and dual processor models, all fans are 4056
Front ports	One XClarity Controller USB, one USB 3.0, one optional VGA
Rear ports	One VGA, two USB 3.0, two ethernet (RJ-45), one XClarity Controller connector. Optional COM port
Environmental specification	Supports ASHRAE A4 with limitations.

Temperature - operating	A4: 5°C to 45°C (41°F to 113°F) A3: 5°C to 40°C (41°F to 104°F) A2: 10°C to 35°C (50°F to 95°F)
Temperature - non operating (no package)	-10°C to 60°C (14°F to 140°F)
Temperature - non operating (with package)	-40°C to 70°C (-40°F to 158°F)
Altitude - operating	(Unpressurized): 0-10000ft (0-3048m)
Humidity - operating, non-condensing	A4: 8%~90%. A3:8%~85%. A2:8%~80%
Humidity - storage (with package), non-condensing	8%~90%

Models should meet the following requirements to support A3 and A4:
- *Redundant power supplies required*
- *No system fan fails*
- *No NVMe drive*
- *No rear two HS bays*
- *Processor TDP is less than or equal to 140 watts, and no Intel Xeon 6140 or 6152 processor is installed*
- *On 12x 3.5" models. mo M.2 drives*

Environmental certification	Energy Star Server 2.1 certified. More environmental information please see: www.lenovo.com/social_responsibility/us/en/environment/



Note: GbE port 1 and LOM port 1 support Wake-on-LAN and NC-SI. Riser cards, expansion cards, and LOM adapters are optional.

Expansion slots

Slot 1-2 (riser card 1)	Supports one of the following for riser card 1: Option 1: PCIe 3.0 x8/x16 (slot 1-2). Low profile for x8, low profile or full height half length for x16 Option 2: PCIe 3.0 x8/x8 ML2 (slot 1-2). Low profile
Slot 3 (riser card 2)	Option 1: PCIe 3.0 x 8, low profile, for single processor model Option 2: PCIe 3.0 x 16, low profile, for dual processor model When slot 2 is full height, slot 3 cannot be used

System unique options

7XH7A05892	ThinkSystem SR530/SR570 x8/x8ML2 PCIe LP+LP Riser 1 Kit
7XH7A02682	ThinkSystem SR530/SR570/SR630 x8/x16 PCIe LP+LP Riser 1 Kit
7XH7A05893	ThinkSystem SR530/SR570/SR630 x8/x16 PCIe LP+FH Riser 1 Kit
7XH7A05891	ThinkSystem SR530/SR570 x8 PCIe LP Riser 2 Kit
7XH7A02685	ThinkSystem SR530/SR570/SR630 x16 PCIe LP Riser 2 Kit
7Z17A02579	ThinkSystem SR530/SR570/SR630 Front VGA Connector Upgrade Kit
7Z17A02581	ThinkSystem 1U Security Bezel
7Z17A02577	ThinkSystem COM Port Upgrade Kit
4XH7A08762	ThinkSystem SR570 2.5" SATA/SAS 8-Bay Backplane Kit

ThinkSystem SR570











