Philips
Digital audio cable

8 ft
Pro Series

SWW1602U





Experience Advanced Sound

with this digital coaxial audio cable

Experience Hi-definition sound while transferring audio signals between your components. Advanced construction delivers superior sound performance.

Enjoy advanced sound quality
- 24 carat gold-plated connectors optimize signal
- 99.97% Oxygen-Free Copper (OFC)
- Split center pin for optimal signal transfer

Enjoy extended durability
- Protective metal shell for extended durability
- Flexible PVC jacket

Protects against signal loss
- Dielectric insulation
- Triple shielding

Environmentally friendly
- Environmentally friendly lead-free construction

PHILIPS

Digital audio cable
8 ft Pro Series

SWW1602U/27

Specifications

Packaging dimensions
- Packaging dimensions (W x H x D): 18.0 x 26.9 x 5.1 cm
- Packaging dimensions (W x H x D): 7.1 x 10.6 x 2 inch
- Nett weight: 0.231 kg
- Nett weight: 0.509 lb
- Gross weight: 0.391 kg
- Gross weight: 0.862 lb
- Tare weight: 0.160 kg
- Tare weight: 0.353 lb
- UPC: 6 09585 18082 6
- Number of products included: 1
- Packaging type: Carton

Outer Carton
- Outer carton (L x W x H): 30.0 x 23.9 x 22.1 cm
- Outer carton (L x W x H): 11.8 x 9.4 x 8.7 inch
- Nett weight: 0.924 kg
- Nett weight: 2.037 lb
- Gross weight: 2.150 kg
- Gross weight: 4.74 lb
- Tare weight: 1.226 kg
- Tare weight: 2.703 lb
- GTIN: 1 06 09585 18082 3
- Number of consumer packagings: 4

Inner Carton
- Inner carton (L x W x H): 27.9 x 10.9 x 20.1 cm
- Inner carton (L x W x H): 11 x 4.3 x 7.9 inch
- Nett weight: 0.462 kg
- Nett weight: 1.019 lb
- Gross weight: 0.880 kg
- Gross weight: 1.94 lb
- Tare weight: 0.418 kg
- Tare weight: 0.921 lb
- GTIN: 2 06 09585 18082 0
- Number of consumer packagings: 2

Highlights

24 carat gold-plated connector
24 carat gold-plated connectors ensure the best signal quality for your components.

99.97% OFC solid conducter
99.97% Oxygen-free copper (OFC) cable core provides optimum signal quality.

Dielectric insulation
Superior insulation material separates the center conductor from the braided shield. By isolating the conductors, it maintains signal integrity, ensuring the best picture quality and optimum data transfer.

Triple shielding
Provides protection against outside noise and interference that can degrade signal clarity.

Metal shell
The metal shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Flexible PVC Jacket
Flexible PVC jacket provided protection to the delicate core of the cable. It also offers extended durability and ease of installation.

split center pin
Split center pin for optimal signal transfer

Lead-free construction
Lead-free construction of environmentally friendly materials.

Issue date 2014-03-14
Version: 1.0.6
12 NC: 8670 000 58557
UPC: 6 09585 18082 6

© 2014 Koninklijke Philips N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com