Product data sheet

Specifications



GUTOR PXC UL Battery Cabinet, 150A Breaker, Premium 205 Watt/ Cell Battery

GUPXCB150EN205

Discontinued

Overview

Presentation	Fully populated, VRLA battery cabinets. Includes all breakers and fuses, line up and match capability, top and/or bottom cable entry.
Lead time	Special Order - Call for Quoted Lead Times

Main

Battery Type	VRLA

Batteries & Runtime

Battery Placement	Battery Cabinet
Battery Slots Empty	0
Included Battery Modules	0
Battery manufacturer	C&D and Enersys
Device mounting	Enclosed battery cabinet
Battery Volt-Amp-Hour Capacity	0 VAh

Physical

Height	82.72 in (210.1 cm)
Width	30.31 in (77 cm)
Depth	31.50 in (80 cm)
Net Weight	1999.99 lb(US) (907.18 kg)
Mounting Mode	Not rack-mountable

Conformance

Standards	FCC Part 15 class A UL 1778

Environmental

Ambient Air Temperature for Operation	14…104 °F (-10…40 °C)
Operating altitude	0...9842 ft
Relative Humidity	0…95 % non-condensing

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Storage	5…104 °F (-15…40 °C)
Storage altitude	0…16404 ft (0.00…4999.94 m)
Storage Relative Humidity	0…95 % non-condensing

Contractual warranty

Warranty	1 year (parts only)

Recommended replacement(s)