Product data sheet

Specifications



GUTOR PXC UL Battery Cabinet, 300A Breaker, Premium 540 Watt/ Cell Battery

GUPXCB300EN540

Discontinued

Overview

Presentation	Fully populated, VRLA battery cabinets. Includes all breakers and fuses, line up and match capability, top and/or bottom cable entry.
Lead time	Special Order - Call for Quoted Lead Times

Main

Battery Type	VRLA

Batteries & Runtime

Battery Placement	Battery Cabinet
Battery Slots Empty	0
Included Battery Modules	0
Battery manufacturer	C&D and Enersys
Device mounting	Enclosed battery cabinet
Battery Volt-Amp-Hour Capacity	0 VAh

Physical

Height	82.72 in (210.1 cm)
Width	39.69 in (100.8 cm)
Depth	31.50 in (80 cm)
Net Weight	4075.01 lb(US) (1848.39 kg)
Mounting Mode	Not rack-mountable

Conformance

Standards	FCC Part 15 class A UL 1778

Environmental

Ambient Air Temperature for Operation	14…104 °F (-10…40 °C)
Operating altitude	0...9842 ft
Relative Humidity	0…95 % non-condensing

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient Air Temperature for Storage	5…104 °F (-15…40 °C)
Storage altitude	0…16404 ft (0.00…4999.94 m)
Storage Relative Humidity	0…95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	90.71 in (230.4 cm)
Package 1 Width	54.02 in (137.2 cm)
Package 1 Length	38.50 in (97.8 cm)
Package 1 Weight	4166.25 lb(US) (1889.779 kg)
Number of Units in Package 3	1

Contractual warranty

Warranty	1 year (parts only)

Recommended replacement(s)