

Rackmount 19" LCD DVI Console

19-Inch LCD Panel, 1U, Modular system, French Layout

Part No.: 508162

This console must be used in conjunction with the singular connection DVI cable set (507905) or the following modular KVM switch 507912.

Features:

- Integrated LCD console, keyboard & mouse
- Manage/control PS/2 or USB computers from one keyboard, monitor and mouse (DVI KVM Module needed)
- Standard 19 inch 1U rack drawer
- Flip-open 19 inch LCD panel supports 1920 x 1080 at 60 Hz
- Gain complete control with easy-to-use OSD interface
- Adjustable—for rack cabinets with depths from 600 mm to 1000 mm (23.6 to 39.37 in.)
- 100-key, low-profile, sturdy keyboard included
- Ergonomic hand rest design
- Ultra-sturdy rear bracket and extension design
- OSD control and adjustment
- Auto-scan automatically selects computers sequentially
- Supports both PS/2 and USB mouse
- Operating system independent, transparent to all applications
- Three-Year Warranty

Specifications:

Standards
• PS/2
• USB

For more information on Intellinet products, consult your local dealer or visit www.intelllinet-network.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

• Compatible with Windows, MAC and Unix

General
• PC connections: Dependent on KVM module purchased alongside
• Computer selection:
- Via buttons
- Via hotkeys
• OSD: yes
• FCC Class B, CE, RoHS

Power
• Input (AC): approx. 100 - 240 V

LCD Panel
• Active display area: 337.9 x 270.3 (mm)
• Pixel pitch: 0.264 (H) x 0.264 (W)
• Resolution: 1920 x 1080 at 60 Hz
• Brightness: 250 (Typ)
• Contrast ratio: 1000:1 (Typ)
• Display color: 16.7M colors
• User control: OSD control (auto saving)
• Backlight unit: LED
• MTBF: 100,000 hours

Keyboard
• Ultra-thin, 100-key, French-layout, stand-alone, removable keyboard (keyboard language format optional)
• Microsoft Windows9, Me/NT/2000/XP, WIN7, Server2003, WIN8, WIN10
• Service life > 1,000,000 times

Mouse
• Touch Mouse
• 1000 point/inch?40 x 40 mm)
• Service life > 1,000,000 times

Environmental
• Operating temperature: 0 – 50°C (32 – 122°F)
• Storage temperature: -20 – 60°C (-4 – 140°F)

Package Contents
• 19" Rackmount Console
• Rear bracket and extension kit
• Power adapter
• User manual

For more information on Intellinet products, consult your local dealer or visit www.intelllinet-network.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.













For more information on Intellinet products, consult your local dealer or visit www.intelllinet-network.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.