

3.5 mm Mic/Headset 1-to-2 Adapter

Stereo, 3.5 mm (CTIA) Four-Position Female to 2 x 3.5mm Three-Position Male; 20 cm (8 in.); Black

Part No.: 354578

High-quality connections that provide superior performance

The Manhattan 3.5 mm Mic/Headset 1-to-2 Adapter connects headphone/microphone combos with combined 3.5 mm, four-pin jacks to two three-pin ports for crisp, clear, error-free transmissions. Whether using with legacy headsets or the newest gaming headset, the Manhattan 3.5 mm Mic/Headset 1-to-2 Adapter is carefully engineered and constructed of quality materials, helping ensure maximum conductivity, minimal degradation and the highest performance from connected media devices.

Features:

- One 3.5 mm, four-pin stereo female to two 3.5 mm, three-pin, stereo male
- Allows Headset with Microphone and four-pin (position) jack to connect to a PC; supports both audio input and output
- Converts separate 3.5 mm, TRS headphone and microphone ports into a 3.5 mm, TRRS connection (this product is not a headphone splitter and will not split to 2 headphones)
- This cable uses CTIA pole configuration, which may result in only the earphones working–not the mic–when used with an OMTP configured device
- For use with headsets with a four-position jack when connecting to separate microphone and audio ports
- Heavy-gauge cable with PVC protective jacket
- Corrosion-resistant contacts for best data transmission
- Heavy-duty strain relief
- Lifetime Warranty

Specifications:

Standards and Certifications
• FCC
• CE
• RoHS2

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

General
• 28 AWG cable
• Housing: ABS plastic
• Weight: 31 g (1.1 oz.)
• Length: 20 cm (8 in.)

Connections
• One 3.5 mm stereo female connection, four-pin, TRRS, CTIA configuration: left audio, right audio, ground, mic
• Two 3.5 mm stereo male connection, three-pin, TRS
headphone configuration: left audio, right audio, ground
microphone configuration: mic, not connected, ground
• Molded PVC boot

Operating Environment
• Operation Temperature: 32 – 104°F (0 – 40°C)
• Storage Temperature: -4 – 140°F (-20 – 60°C)
• Humidity (noncondensing): 5 – 90%

Package Contents
• 3.5 mm Mic/Headset 1-to-2 Adapter







For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.





For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.
All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.