Specifications







Eaton 9PXM8S8K-PD

Eaton 9PXM UPS, 8 kVA scalable to 16 kVA, Hardwired input, Outputs: (4) 5-20R, (2) L6-30R, 208-240V, Rack/Tower, 14U

General specifications	
PRODUCT NAME	Eaton 9PXM UPS
CATALOG NUMBER	9PXM8S8K-PD
UPC	786689053437
PRODUCT LENGTH/DEPTH	34.5 in
PRODUCT HEIGHT	25 in
PRODUCT WIDTH	17.5 in
PRODUCT WEIGHT	333 lb
COMPLIANCES	TAA Compliant ICES-003 FCC Compliant
CERTIFICATIONS	cULus Listed 72/23/EEC 93/68/EEC 89/336/EEC92/31/EEC IEC 60950 IEC 62040-1 EMC: IEC 62040-2 IEC Rated
PRODUCT TYPE	UPS

Powering Business Worldwide

Battery

RUNTIME GRAPH	View runtime graph
BATTERY REPLACEMENT	Hot-swappable internal batteries and extended battery modules (EBMs)
BATTERY MANAGEMENT	ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)
EXTENDED BATTERY CAPABILITY	Yes

Electrical input

INPUT CONNECTION	Hardwired
INPUT NOMINAL VOLTAGE	110V/220V, 120V/208V, 120V/240V, 127V/220V
INPUT POWER FACTOR	>0.99 typical
INPUT FREQUENCY RANGE	60 Hz: 50–70 Hz

Electrical output

RECEPTACLE	(8) 5-20R, (2) L6-30R, (2) L6-20R, (2) L14-30R, Hardwired
OUTPUT FREQUENCY	60 Hz
VOLTAGE	120/208V
OUTPUT NOMINAL VOLTAGE	110V/220V, 120V/208V, 120V/240V, 127V/220V
VA RATING	8 kVA
WATTAGE	7.2 kW
OUTPUT WAVEFORM	True sine wave
OUTPUT POWER FACTOR	0.9
TOPOLOGY	Online/Double-conversion

Communications

EXPANSION SLOTS	• (2) Mini-Slot (MS) expansion ports. The following optional connectivity cards may be ordered separately. • Gigabit Network Card part number: NETWORK-M2 • Modbus card part number: INDGW-M2 • Relay card part number: RELAY-MS
SOFTWARE COMPATIBILITY	Intelligent Power Software Suite

Environmental

TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
RELATIVE HUMIDITY	5-95% non-condensing

Additional specifications

PACKAGE CONTENTS	• 9PXM8S8K-PD 9PXM 8000VA 7200W 208/240V Online Double-Conversion UPS • (2) 9PXMSPPM 9PXM split-phase power modules • (4) 9PXMBAT 9PXM internal battery modules • NETWORK-M2 Gigabit network card • Owner's manual
INTERNAL BYPASS	Yes

AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black/silver
HOT SWAP POWER	Yes

Warranty and support

STANDARD FACTORY WARRANTY	• 2-YEAR FACTORY WARRANTY • - 2 years • Parts, labor, electronics and batteries coverage* • - Startup included • - Parts, electronics and batteries coverage • - Standard ground shipping • - Technical support • *if startup is performed by Eaton, if self-performed startup then just 90 days labor
EXTENDED SERVICE PLANS	• ADVANCED DEPOT EXCHANGE • - 5-year depot repair: 9SW5Y-11000UC • - Expedited parts coverage for 5 years • - Parts, electronics and UPS batteries coverage • - Next business day shipping • - Technical support • • 5-YEAR ON-SITE PLAN: WFLN75XX-11000UC • - On-site parts and labor coverage for years 5 • - Parts, electronics and UPS batteries coverage • - 24x7 on-site labor coverage, next-day response • - Next-day shipping • - Technical support

Resources

BROCHURES	9PXM UPS brochure
DRAWINGS	Eaton 9PXM UPS CTO guide Eaton 9PXM UPS 8-slot 2D drawing
MANUALS AND USER GUIDES	9PXM user guide
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 9PXM8S8K-PD

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.