SP 330 series

# SP 330DN
# SP 330SN
# SP 330SFN

RICOH
imagine. change.




## SP 330 series specifications

The SP330 series offers the solution that is right for your needs, whether it's just easy-to-manage and compact printing, or multifunction productivity. Compact footprints make these solutions ideal for smaller spaces and maintenance and management are simple, with intuitive operation.

**Features for printers in this series include:**

- Crisp 32 pages per minute output
- SP 330DN is ideal for use on desktops or under counters
- SP 330SN provides printing, scanning and copying
- SP 330SFN comes with 4.3 inch touch panel and ARDF

# SP 330DN/SP 330SN/SP 330SFN

MAIN SPECIFICATIONS

| | SP 330DN | SP 330SN | SP 330SFN |
|---|---|---|---|
| **GENERAL** | | | |
| Warm-up time (sec.) | 26 | 30 | 30 |
| First output speed: B/W (sec.) | | 7.5 | |
| Continuous output speed (ppm) | | 32 | |
| Memory: standard (MB) | 128 | 256 | 256 |
| Weight (kg) | 13 | 18 | 18 |
| Dimensions: W x D x H (mm) | 370 x 392 x 262 | 405 x 392 x 407 | 405 x 392 x 420 |
| Power source | | 220 - 240 V, 50/60 Hz | |
| Laser classification | | Class 1 Laser Product (IEC60825 - 1:2014) | |
| **COPIER (SP 330SN, SP 330SFN)** | | | |
| Multiple copying | - | Up to 99 copies | Up to 99 copies |
| Resolution | - | 1,200 x 1,200 dpi | 1,200 x 1,200 dpi |
| Enlargement/reduction | | 25 - 400% | |
| Zoom | - | From 25% to 400% in 1% steps | From 25% to 400% in 1% steps |
| **PRINTER** | | | |
| Printer language: standard | | PCL5e (Mac OS), PCL6 (Windows), PostScript 3 | |
| Print resolution: maximum (dpi) | | 1,200 x 1,200 | |
| Network interface: standard | | Ethernet 10 base-T/100 base-TX, USB2.0 Type B | |
| Network interface: option | | Wireless LAN (IEEE 802.11 a/b/g/n/ac) | |
| Windows® environments | | Windows® 7/8.1/10, Windows® Server 2008/2012/2012R2/2016 | |
| Mac OS environments | | Macintosh OS X v10.10 or later | |
| Other supported environments | | Linux environment | |
| **SCANNER (SP 330SN, SP 330SFN)** | | | |
| Scanning: B/W (ipm) | - | 13 | 13 |
| Scanning: full colour (ipm) | - | 4.5 | 4.5 |
| Resolution: maximum (dpi) | - | 600 | 600 |
| **FAX (SP 330SFN)** | | | |
| Compatibility | - | - | ITU-T (CCITT) G3 |
| Transmission speed (seconds) | - | - | 3 |
| Modem speed: maximum (Kbps) | - | - | 33.6 |
| **PAPER HANDLING** | | | |
| Recommended paper size | | A4, A5, A6, B5, B6 | |
| Paper input: standard (sheets) | | 300 | |
| Paper input: maximum (sheets) | | 550 | |
| Paper output: standard (sheets) | 125 | 50 | 50 |
| Paper weight (g/m²) | | 52 - 162 | |
| **ECOLOGY** | | | |
| Power consumption: max. (kWh) | | Less than 1.025 | |
| Power consumption: sleep (W) | 0.72 | 0.87 | 0.87 |
| TEC (kWh)* | 0.41 | 0.42 | 0.42 |

* It is a reference value based on the ENERGY STAR Ver.3.0 test method.

**OPTIONS**

1x 250-sheet Paper tray, IEEE 802.11 a/b/g/n/ac

**CONSUMABLES**

| | |
|---|---|
| Starter toner (prints) | 1,000 |
| Toner (regular yield) (prints) | 3,500 |
| Toner (high yield) (prints) | 7,000 |
| Consumable yield measuring method ISO/IEC 19752 | |

ISO9001 certified, ISO14001 certified, ISO27001 certified

COMMISSION REGULATION (EU) 2019/2020. The light source of this product is not intended for applications other than image printing.


## Ricoh UK Ltd.

300 and 800 Pavilion Drive Northampton Business Park
NN4 7YL Northampton
United Kingdom

+44(0)1604 814900

www.ricoh.co.uk


RICOH imagine. change.

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2021 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.