CAT. N° 4 149 30



STATE REPORTING MODULES CX³ - UNIVERSAL SIGNALLING - 3 LED LIGHTS - 1 MODULE

Pack (number of units)	1
Volume (dm³)	0,219
Weight (g)	62,00

Product characteristics

State reporting modules

Universal signalling module

- Enables upstream busbar connection
- Equipped with 3 LED lights: green, red and yellow
- Indicates various type of information, according to selected configuration:
- contacts position, plugged-in or drawn-out product, etc…
- Equipped with DIP switches (on the side) allowing product configuration: selection of information type and of the LED behaviour
- Compatible with symmetrical rail mounting protection devices or head equipment (DMX³ and DPX³)
- Consumption: 0.377 W - 31.4 mA (12 V =)
- Number of modules : 1

General characteristics

CX³ energy management system

- Conform to IEC/EN 61131-2 (Programmable controllers)
- CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone") or remotely
- All the modules of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)
- Power supply with specific module Cat.No 4 149 45
- Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Documentation

Catalogue pages & additional information

- Description page (p.100)

Installation & technical data

- F02332EN-03
- ModbusTable_EMS_414930_Break Posit_v1
- ModbusTable_EMS_414930_Break Stat_v1
- ModbusTable_EMS_414930_Contactor_v1
- ModbusTable_EMS_414930_Gen Input_v1
- ModbusTable_EMS_414930_Spring Stat_v1
- Instal-Manual-RA00163AB-EN
- MODBUS TABLE EMS 414930 State Breaker
- MODBUS TABLE EMS 414930 State GenericInput
- MODBUS TABLE EMS 414930 State Position
- MODBUS TABLE EMS 414930 State Spring

Installation instructions & related documents

- LE08383AC

Softwares

- Legrand Energy Management Software

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.