Specifications

Eaton 9SX700I-AU

Eaton 9SX UPS, AU, Tower, 700VA, 630W, 240VAC, Input: IEC C14, Output: AUS 10A x 4, builit-in battery, Multilingual graphical LCD display

General specifications	
PRODUCT NAME	Eaton 9SX UPS
CATALOG NUMBER	9SX700I-AU
PRODUCT LENGTH/DEPTH	160 mm
PRODUCT HEIGHT	252 mm
PRODUCT WIDTH	357 mm
PRODUCT WEIGHT	11.5 kg
COMPLIANCES	CB CE Marked RCM
CERTIFICATIONS	IEC 61000-4 EN 62040-3 IEC/EN 62040-1 IEC/EN 62040-2

Powering Business Worldwide

Product specifications

TOPOLOGY	Online/Double-conversion
CONSTRUCTION TYPE	Free standing model
COLOR	Black
VA RATING	700 VA
WATTAGE	630 W
INTERNAL BYPASS	Yes
HOT SWAP POWER	No
AUTO SHUTDOWN FUNCTION	Yes
INPUT NOMINAL VOLTAGE	240V
NOMINAL FREQUENCY	50/60 Hz
INPUT FREQUENCY RANGE	40-70 Hz
RECEPTACLE	AUS 10A x 4
OUTPUT WAVEFORM	Sine wave
VOLTAGE	240V
OUTPUT NOMINAL VOLTAGE	240V
VOLTAGE TYPE	AC
RUNTIME GRAPH	View runtime graph
BATTERY REPLACEMENT	Hot swappable
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Yes
EXPANSION SLOTS	One slot for optional communication card
INCLUDES NETWORK CARD	No
SOFTWARE COMPATIBILITY	Eaton Intelligent Power Manager, Eaton Intelligent Power Protector
USER INTERFACE	Multilingual graphical LCD display
ALTITUDE	<1000m for nominal power, 10% power degrading every 1000m (up to 3000m)
NOISE LEVEL	<40 dB at 1 meter
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)
INPUT VOLTAGE RANGE	190-276 Vac without derating (up to 120-276 Vac with derating)
OUTPUT FREQUENCY	50/60 Hz

Resources

OUTPUT POWER FACTOR	0.9
PHASE (INPUT)	Single-phase
PHASE (OUTPUT)	Single-phase

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.