CAT. N° 6 468 42



19" PDU LCS³ - 1U - 6 X 2P+E - ITALIAN STANDARD - WITH AMMETER

Unit price ex. taxes	O/R
Pack (number of units)	1
Volume (dm³)	2,431
Weight (g)	996,00

Product characteristics

19" - PDU with ammeter

- Measure consumption to provide better installation management: balancing circuits, displaying available capacity, preventing overloads and power failures
- Measure total PDU current
- Rotating display to ensure a perfect reading whatever the PDU mounting direction is (horizontal, vertical with top or bottom power supply input)

Italian standard

- 6 outlets

General characteristics

Legrand cabling system LCS³ Energy Distribution - 1U Power Distribution Units

- To provide ~ electric power for IT equipment in 19" enclosures
- 230 V - 50/60 Hz power supply
- 1U aluminium profile
- End cap with metallic brackets and cable holder shape
- Quick fixing (no screws) on 19" fixing centers. Can also be installed vertically by reverting the brackets (no screws)
- 2P+E outlets:
  - C13 and C19 standard outlets are equipped with cord locking system to avoid any accidental disconnection. Universal solution compatible with all the cords (C14 plugs for C13 and C20 plugs for C19)
  - French, German and British standard outlets are equipped with blanks
  - French and German standard outlets are inclined at 55°
- Black modules (outlets and functions)

Documentation

Catalogue pages & additional information

- Selection chart (p.725)
- Description page (p.772)
- Technical page (p.779)

Installation & technical data

- S000093176EN-05

Installation instructions & related documents

- LE09269AA_02

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.