PHILIPS

Lighting



StoreSet

RC505B LED66S/830 PSU WB WH W3

StoreSet Recessed - 830 warm white - Power supply unit - Wide beam - Plug-in connector 3-pole Wieland/Adels compatible - White

Today's retail stores are all about creating experiences in order to attract and retain visitors. StoreSet adds atmosphere to your store by introducing contrast and breaking up the traditional continuous light-lines. A variety of beam shapes, combined with excellent light quality, ensures the merchandise stands out, whilst at the same time enabling you to create your chosen ambience. StoreSet is lightweight and can be easily connected to power tracks. Installation is straightforward, and if your needs change, you can simply adapt the lighting by repositioning the fixtures along the track. This makes StoreSet a truly flexible tool for setting store ambiance.

Product data

General Information	
Beam angle of light source	120 °
Light source color	830 warm white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	Power supply unit
Driver included	Yes
Optic type	Wide beam
Luminaire light beam spread	40°
Connection	Plug-in connector 3-pole Wieland/Adels compatible
Cable	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 5 s

Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
ENEC mark	ENEC mark
Warranty period	5 years
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore the median useful life (B50) value also represents the B10 value.
Constant light output	No
Number of products on MCB of 16 A type B	24

StoreSet

RoHS mark	RoHS mark
Product family code	RC505B [StoreSet Recessed]
Unified glare rating CEN	Not applicable

Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Inrush current	19 A
Inrush time	0.275 ms
Power Factor (Min)	0.9

Controls and Dimming

Dimmable	No

Mechanical and Housing

Housing Material	Metal
Reflector material	Polycarbonate aluminum coated
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Optical cover/lens finish	Clear
Overall length	622 mm
Overall width	214 mm
Overall height	65 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	6600 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	132 lm/W
Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	80
Initial chromaticity	(0.43, 0.40) SDCM<3
Initial input power	50 W
Power consumption tolerance	+/-10%

Application Conditions

Ambient temperature range	+10 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes (relates to presence/ movement detection and daylight harvesting)

Product Data

Full product code	871869917221300
Order product name	RC505B LED66S/830 PSU WB WH W3
EAN/UPC - Product	8718699172213
Order code	910500459746
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910500459746
Net Weight (Piece)	3.000 kg

Dimensional drawing



StoreSet recessed RC505B



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com
2019, February 11 - data subject to change