PHILIPS

Lighting



Maxos LED Performer

4MX900 LED90S/840 PSD MB WH L1800

Maxos LED Performer - Generation 3 - LED module, system flux 9000 lm - 840 neutral white - Power supply unit with DALI interface - Medium beam - White

Customers want to save energy and reduce cost compared to what they are used to with conventional lighting. At the same time, excellent lighting conditions are needed: in industrial environments, to guarantee safety and productivity; and in retail environments, to make the merchandise stand out and attract shoppers.Maxos LED Performer is an extremely flexible solution that delivers low energy consumption and excellent beam shaping at an attractive investment level.

Product data

General Information	
Number of light sources	1 [1 pc]
Lamp family code	LED90S [LED module, system flux 9000 lm]
Beam angle of light source	120 °
Light source colour	840 neutral white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	PSD [Power supply unit with DALI interface]
Driver included	Yes
Optic type	MB [Medium beam]
Luminaire light beam spread	70°
Emergency lighting	No [-]
Control interface	DALI
Connection	CU5 [Connection unit 5-pole]
Cable	-
Protection class IEC	Safety class I (I)

Glow-wire test	650/30 [Temperature 650 °C, duration 30 s]
Flammability mark	D [For mounting on easily flammable surfaces]
CE mark	CE mark
ENEC mark	ENEC mark
Warranty period	5 years
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore the median useful life (B50) value also represents the B10 value.
Constant light output	No
Number of products on MCB	18
RoHS mark	RoHS mark

Maxos LED Performer

Product Family Code	4MX900 [Maxos LED Performer]
Unified glare rating CEN	Not applicable

Operating and Electrical

Input voltage	220 to 240 V
Input frequency	50 to 60 Hz
Control signal voltage	0-16 V DC DALI
Inrush current	4.5 A
Inrush time	0.065 ms
Power factor (min.)	0.9

Controls and Dimming

Dimmable	Yes

Mechanical and Housing

Trunking length	No [-]
Housing material	Aluminum
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover/lens material	Polymethyl methacrylate
Fixation material	Steel
Optical cover/lens finish	Clear
Overall length	1800 mm
Overall width	87 mm
Overall height	82 mm

Approval and Application

Ingress protection code	IP40 [Wire-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Initial Performance (IEC Compliant)

Initial luminous flux	9000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	134 lm/W
Init. Corr. colour temperature	4000 K
Init. colour rendering index	≥80
Initial chromaticity	(0.38, 0.38) SDCM <3.5
Initial input power	67 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L80


Application Conditions

Ambient temperature range	-20 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dimming level	1%
Suitable for random switching	Not applicable


Product Data

Full product code	403073266461099
Order product name	4MX900 LED90S/840 PSD MB WH L1800
EAN/UPC – product	4030732664610
Order code	66461099
Numerator – quantity per pack	1
Numerator – packs per outer box	2
Material no. (12NC)	910629138926
Net weight (piece)	2.900 kg

Dimensional drawing



Maxos LED Performer 4MX900-933



Maxos LED Performer 4MX900-933



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com
2019, March 14 - data subject to change