

Maxos LED Performer

4MX900 491 LED50S/840 PSU DA30 WH

Maxos LED Performer - Generation 3 - 1 unit for TL5 49 W - LED Module, system flux 5000 lm - 840 neutral white - Power supply unit - Double asymmetric optic 30° - White

Customers want to save energy and reduce cost compared to what they are used to with conventional lighting. At the same time, excellent lighting conditions are needed: in industrial environments, to guarantee safety and productivity; and in retail environments, to make the merchandise stand out and attract shoppers.Maxos LED Performer is an extremely flexible solution that delivers low energy consumption and excellent beam shaping at an attractive investment level.

Product data

General Information	
Number of light sources	1 [1 pc]
Lamp family code	LED50S [LED Module, system flux 5000 lm]
Beam angle of light source	120 °
Light source colour	840 neutral white
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	PSU [Power supply unit]
Driver included	Yes
Optic type	DA30 [Double asymmetric optic 30°]
Luminaire light beam spread	30°
Emergency lighting	No [-]
Connection	Connection unit 3-pole
Cable	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s

Flammability mark	D [For mounting on easily flammable surfaces]
CE mark	CE mark
ENEC mark	ENEC mark
Warranty period	5 years
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore the median useful life (B50) value also represents the B10 value.
Constant light output	No
Number of products on MCB	24
RoHS mark	RoHS mark
Product Family Code	4MX900 [Maxos LED Performer]

Maxos LED Performer

Unified glare rating CEN	Not applicable

Operating and Electrical

Input voltage	220 to 240 V
Input frequency	50 to 60 Hz
Control signal voltage	0-16 V DC DALI
Inrush current	17.8 A
Inrush time	0.282 ms
Power factor (min.)	0.9

Controls and Dimming

Dimmable	No

Mechanical and Housing

Trunking length	491 [1 unit for TL5 49 W]
Housing material	Aluminium
Reflector material	-
Optic material	Polymethyl methacrylate
Optical cover/lens material	Polymethyl methacrylate
Fixation material	Steel
Optical cover/lens finish	Clear
Overall length	1479 mm
Overall width	87 mm
Overall height	82 mm

Approval and Application

Ingress protection code	IP40 [Wire-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Initial Performance (IEC Compliant)

Initial luminous flux	5000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	141 lm/W
Init. Corr. colour temperature	4000 K
Init. colour rendering index	≥80
Initial chromaticity	(0.38, 0.38) SDCM <3.5
Initial input power	35.5 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L80

Application Conditions

Ambient temperature range	-20 to +40 °C
Performance ambient temperature Tq	25 °C
Suitable for random switching	Not applicable

Product Data

Full product code	403073266727799
Order product name	4MX900 491 LED50S/840 PSU DA30 WH
EAN/UPC – product	4030732667277
Order code	66727799
Numerator – quantity per pack	1
Numerator – packs per outer box	2
Material no. (12NC)	910629170126
Net weight (piece)	2.345 kg

Dimensional drawing



Maxos LED Performer 4MX900-933

Maxos LED Performer

Photometric data



IFGU1_4MX900 G3 491 1xLED50S840 PSU DA30.EPS



IFPC1_4MX900 G3 491 1xLED50S840 PSU DA30.EPS

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.