

# LuxSpace Accent

## RS741B LED27S/930 PSE-E MB WH

LuxSpace Accent Compact G3 - LED Module, system flux 2700 lm - 930 warm white - Power supply unit external, DC compatible for central emergency lighting - Medium beam - White

Retailers are increasingly having to contend with rising energy prices. At the same time, they need to retain the quality of light they are used to, flexibility in architectural integration, and the right light effects to catch the customer's eye. Last but not least, they need future-proof solutions that will enable them to implement differentiating concepts in their store. Delivering high-quality light, punch in the beam and outstanding luminous efficacy, LuxSpace Accent is the ideal energy-efficient solution for today's demanding retail environments, covering a wide variety of lighting applications, including CrispWhite for fashion stores and Food recipes for supermarkets.

### Product data

| General Information | |
|---|---|
| **Number of light sources** | 1 [ 1 pc] |
| **Lamp family code** | LED27S [ LED Module, system flux 2700 lm] |
| **Beam angle of light source** | 120 ° |
| **Light source colour** | 930 warm white |
| **Light source replaceable** | No |
| **Number of gear units** | 1 unit |
| **Driver/power unit/transformer** | PSE-E [ Power supply unit external, DC compatible for central emergency lighting] |
| **Driver included** | Yes |
| **Optic type** | MB [ Medium beam] |
| **Optical cover/lens type** | No [ -] |

| | |
|---|---|
| **Luminaire light beam spread** | 24° |
| **Control interface** | - |
| **Connection** | PIP [ Push-in connector and pull relief] |
| **Cable** | - |
| **Protection class IEC** | Safety class II (II) |
| **Glow-wire test** | 650/5 [ Temperature 650 °C, duration 5 s] |
| **Flammability mark** | F [ For mounting on normally flammable surfaces] |
| **CE mark** | CE mark |
| **ENEC mark** | ENEC mark |
| **UL mark** | - |
| **Warranty period** | 5 years |

# LuxSpace Accent

| | |
|---|---|
| **Remarks** | *-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore the median useful life (B50) value also represents the B10 value. |
| **Constant light output** | No |
| **Number of products on MCB** | 32 |
| **RoHS mark** | RoHS mark |
| **Product Family Code** | RS741B [ LuxSpace Accent Compact G3] |

## Operating and Electrical

| | |
|---|---|
| **Input voltage** | 220 to 240 V |
| **Input frequency** | 50 to 60 Hz |
| **Initial CLO power consumption** | - W W |
| **Average CLO power consumption** | - W W |
| **Inrush current** | 14.5 A |
| **Inrush time** | 0.22 ms |
| **Power factor (min.)** | 0.9 |

## Controls and Dimming

| | |
|---|---|
| **Dimmable** | No |

## Mechanical and Housing

| | |
|---|---|
| **Housing material** | Aluminum |
| **Reflector material** | Polycarbonate aluminum coated |
| **Optic material** | Polycarbonate |
| **Optical cover/lens material** | Polycarbonate |
| **Fixation material** | - |
| **Optical cover/lens finish** | Clear |
| **Overall height** | 126 mm |
| **Overall diameter** | 130 mm |

## Approval and Application

| | |
|---|---|
| **Ingress protection code** | IP20 [ Finger-protected] |
| **Mech. impact protection code** | IK02 [ 0.2 J standard] |

## Initial Performance (IEC Compliant)

| | |
|---|---|
| **Initial luminous flux** | 2700 lm |
| **Luminous flux tolerance** | +/-10% |
| **Initial LED luminaire efficacy** | 105.88235294117646 lm/W |
| **Init. Corr. colour temperature** | 3000 K |
| **Init. colour rendering index** | ≥90 |
| **Initial chromaticity** | (0.43, 0.40) SDCM <3 |
| **Initial input power** | 25.5 W |
| **Power consumption tolerance** | +/-10% |

## Over Time Performance (IEC Compliant)

| | |
|---|---|
| **Control gear failure rate at median useful life 50000 h** | 5 % |
| **Lumen maintenance at median useful life* 50000 h** | L80 |


## Application Conditions

| | |
|---|---|
| **Ambient temperature range** | +10 to +40 °C |
| **Performance ambient temperature Tq** | 25 °C |
| **Suitable for random switching** | Yes (relates to presence/ movement detection and daylight harvesting) |

## Product Data

| | |
|---|---|
| **Full product code** | 871869684816600 |
| **Order product name** | RS741B LED27S/930 PSE-E MB WH |
| **EAN/UPC – product** | 8718696848166 |
| **Order code** | 84816600 |
| **Numerator – quantity per pack** | 1 |
| **Numerator – packs per outer box** | 1 |
| **Material no. (12NC)** | 910500457339 |
| **Net weight (piece)** | 0.740 kg |


## Dimensional drawing





**LuxSpace Accent RS730B-RS752B**

# LuxSpace Accent


## Photometric data




IFAS1_RS741B1xLED27S930MB




IFCC1_RS741B1xLED27S930MB




IFPC1_RS741B1xLED27S930MB

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.