


PowerBalance Tunable White, recessed

RC464B LED80S/TWH PSD W60L60 VPC W

PowerBalance recessed Tuneable WH - LED Module, system flux 8000 lm - Tunable white - Power supply unit with DALI interface - Width 0.60 m, length 0.60 m - Visible profile ceiling version - Plug-in connector 3-pole Wieland/Adels compatible

The right light can have a favourable effect on various physiological processes in the human body. Statistically, 65% of office workers don't feel at their best before 9.00 a.m. By giving them personal control over the lighting in their work space, so they can tailor it to suit the time of day and what they are doing, our PowerBalance Tunable White solution can enhance their comfort, task performance and productivity. Similarly, in schools, PowerBalance Tunable White allows teachers to create the right mood to help pupils to concentrate, relax, etc., depending on the activity at hand, and so perform better overall.

Product data

General Information	
Number of light sources	1 [1 pc]
Lamp family code	LED80S [LED Module, system flux 8000 lm]
Light source colour	Tunable white
Cap base	- [-]
Light source replaceable	No
Number of gear units	1 unit
Gear	-

Driver/power unit/transformer	PSD [Power supply unit with DALI interface]
Driver included	Yes
Optic type	No [-]
Optical cover/lens type	PC [Polycarbonate bowl/cover]
Luminaire light beam spread	86°
Emergency lighting	No [-]
Embedded control	No [-]
Control interface	DALI

PowerBalance Tunable White, recessed

Connection	Plug-in connector 3-pole Wieland/Adels compatible
Cable	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 850 °C, duration 5 s
Flammability mark	F [For mounting on normally flammable surfaces]
Safety bracket	-
Safety device	No [-]
CE mark	CE mark
ENEC mark	ENEC plus mark
UL mark	No
Warranty period	3 years
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore the median useful life (B50) value also represents the B10 value.
Constant light output	No
Number of products on MCB	20
RoHS mark	RoHS mark
Accessory PFC	N/A
Product Family Code	RC464B [PowerBalance recessed Tuneable WH]
Unified glare rating CEN	19

Operating and Electrical

Input voltage	220-240 V
Input frequency	50 to 60 Hz
Control signal voltage	0-16 V DC DALI
Inrush current	5 A
Inrush time	1 ms
Power factor (min.)	0.9

Controls and Dimming

Dimmable	Yes

Mechanical and Housing

Geometry	Width 0.60 m, length 0.60 m
Housing configuration	VPC [Visible profile ceiling version]
Housing material	Composite materials
Reflector material	Polycarbonate
Optic material	-
Optical cover/lens material	Polycarbonate
Gear tray material	Steel
Fixation material	-
Optical cover/lens finish	Matt
Overall length	597 mm
Overall width	597 mm
Overall height	86 mm

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Initial Performance (IEC Compliant)

Initial luminous flux	8000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	110 lm/W
Init. Corr. colour temperature	2700 to 6400 K
Init. colour rendering index	≥80
Initial chromaticity	(0.31, 0.32) SDCM <3 to (0.43, 0.40) SDCM <3
Initial input power	73 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L90

Application Conditions


Ambient temperature range	+10 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dimming level	1%
Suitable for random switching	No

Product Data

Full product code	871869687465300
Order product name	RC464B LED80S/TWH PSD W60L60 VPC W
EAN/UPC – product	8718696874653
Order code	87465300
Numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12NC)	910502042603
Net weight (piece)	5.300 kg


PowerBalance Tunable White, recessed

Dimensional drawing




PowerBalance RC460B-RC468B


Photometric data




IFGU1_RC464BG2PSDW60L601xLED80STWH-2700



IFPC1_RC464BG2PSDW60L601xLED80STWH-2700




IFGU1_RC464BG2PSDW60L601xLED80STWH-3000




IFPC1_RC464BG2PSDW60L601xLED80STWH-3000

PowerBalance Tunable White, recessed


Photometric data




IFGU1_RC464BG2PSDW60L601xLED80STWH-4000




IFPC1_RC464BG2PSDW60L601xLED80STWH-4000




IFGU1_RC464BG2PSDW60L601xLED80STWH-4500



IFPC1_RC464BG2PSDW60L601xLED80STWH-4500




IFGU1_RC464BG2PSDW60L601xLED80STWH-5000




IFPC1_RC464BG2PSDW60L601xLED80STWH-5000

PowerBalance Tunable White, recessed


Photometric data




IFGU1_RC464BG2PSDW60L601xLED80STWH-6000



IFPC1_RC464BG2PSDW60L601xLED80STWH-6000



IFGU1_RC464BG2PSDW60L601xLED80STWH-6300



IFPC1_RC464BG2PSDW60L601xLED80STWH-6300

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.