

TrueLine, suspended

SP532P LED77S/840 PSD ACL SM2 L1450 ALU

TrueLine DIRECT/INDIRECT OC - LED Module, system flux 7700 lm - 840 neutral white - Power supply unit with DALI interface - ActiLume - Push-in connector 5-pole - Suspension set 2-wire - 1450 mm

Architects need a lighting solution that matches the interior architecture of the property that they are working on. They want a light line with an elegant design and very high light levels. Specifiers need luminaires that enable them to save energy, while also providing the right level of light, in compliance with office-lighting regulations. TrueLine suspended is able to meet both sets of requirements. TrueLine is also available in recessed and surface-mounted versions.

Product data

General Information	
Number of light sources	1 [1 pc]
Lamp family code	LED77S [LED Module, system flux 7700 lm]
Light source colour	840 neutral white
Cap base	- [-]
Light source replaceable	No
Number of gear units	1 unit
Gear	Gear tray (without gear)
Driver/power unit/transformer	PSD [Power supply unit with DALI interface]
Driver included	Yes
Optic type	No [-]
Optical cover/lens type	PM [PMMA bowl/cover]
Luminaire light beam spread	100°
Embedded control	ACL [ActiLume]
Control interface	DALI

Connection	Push-in connector 5-pole
Cable	Cable 1.7 m without plug 5-pole PVC silver
Protection class IEC	Safety class I
Mounting	SM2 [Suspension set 2-wire]
Standard RAL colour	-
Glow-wire test	Temperature 650 °C, duration 5 s
Flammability mark	F [For mounting on normally flammable surfaces]
Type description	OC [Office compliant version]
CE mark	CE mark
ENEC mark	ENEC plus mark
UL mark	No
Warranty period	5 years
Remarks	*-Per Lighting Europe guidance paper “Evaluating performance of LED based

TrueLine, suspended

	luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore the median useful life (B50) value also represents the B10 value.
Constant light output	No
Number of products on MCB	24
RoHS mark	RoHS mark
WEEE mark	WEEE mark
Accessory PFC	N/A
Product Family Code	SP532P [TrueLine DIRECT/INDIRECT OC]
Unified glare rating CEN	16

Operating and Electrical

Input voltage	220 to 240 V
Input frequency	50 to 60 Hz
Control signal voltage	0-16 V DC DALI
Inrush current	19 A
Inrush time	0.28 ms
Power factor (min.)	0.9

Controls and Dimming

Dimmable	yes

Mechanical and Housing

Housing material	Aluminium
Reflector material	-
Optic material	-
Optical cover/lens material	Polymethyl methacrylate
Gear tray material	Steel
Fixation material	Stainless steel
Optical cover/lens finish	Frosted
Overall length	1449 mm
Overall width	55 mm
Overall height	121 mm
Length	1450 mm

Approval and Application

Ingress protection code	IP40 [Wire-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Initial Performance (IEC Compliant)

Initial luminous flux	7700 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	126 lm/W
Init. Corr. colour temperature	4000 K
Init. colour rendering index	≥80
Initial chromaticity	(0.38, 0.38) SDCM <3
Initial input power	61 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L85

Application Conditions

Ambient temperature range	+10 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dimming level	1%
Suitable for random switching	Yes (relates to presence/ movement detection and daylight harvesting)

Product Data

Full product code	871869687433200
Order product name	SP532P LED77S/840 PSD ACL SM2 L1450 ALU
EAN/UPC – product	8718696874332
Order code	87433200
Numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12NC)	910504100603
Net weight (piece)	4.200 kg

TrueLine, suspended

Dimensional drawing



TrueLine suspended SP530P-SP533P

Photometric data



IFGU1_SP532PL14501xLED77S840OC



IFPC1_SP532PL14501xLED77S840OC

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.