





**Product Overview:**

High-performance full tower case with a full tempered glass left side panel and front panel to showcase the inside of your rig. Comes equipped with three 14cm Edge Addressable RGB fans in the front panel and one 14cm Edge Addressable RGB fan in the rear of the case. Addressable RGB fans can be controlled using one of three ways: RGB LED control button on top of the case, RGB remote control, or Addressable RGB motherboard. Includes a 10-port hub with PWM control functions.

Specifications

| Model | |
|---|---|
| Case Type | Full Tower |
| Color | Black |
| Body Material | SPCC |
| Front Panel Material | ABS |
| Steel Thickness | 0.7mm |
| Motherboards | E-ATX/ATX/micro-ATX/mini-ITX |
| Case Dimensions (Internal) | 236 x 550 x 425mm (W x H x D) |
| Case Dimensions (Overall) | 249.5 x 566 x 473mm (W x H x D) |
| 5.25” Drive Bays | 0 |
| 3.5” Drive Bays | 2 Max. (2 x 3.5”/2.5") |
| 2.5” Drive Bays | 4 Max. (2 x 2.5” and 2 x 2.5”/3.5”) |
| Expansion Slots | 9 |
| GPU Clearance | Supports GPU up to 383mm |
| CPU Clearance | Supports CPU up to 189mm |
| Air Cooling | Front: 120mm x 4 or 140mm x 3 or 200mm x 2 (Includes 140mm RGB Fan x 3)<br>Rear: 120mm x 2 or 140mm x 2 (Includes 140mm RGB Fan x 1)<br>Bottom: 120mm x 3 or 140mm x 2 (Optional)<br>PSU: 120mm x 3 or 140mm x 2 (Optional) |
| Liquid Cooling | Front: 360mm/480mm Radiator (Optional)<br>Rear: 240mm/280mm Radiator (Optional)<br>Bottom: 240mm/280mm Radiator (Optional)(Fan + Radiator: Thickness<52mm)<br>PSU: 240mm/280mm Radiator (Optional) |
| I/O Ports | USB3.0 x 2 \| USB2.0 x 2 \| HD Audio & Mic. |
| Net Weight/Gross Weight | 11kg (24.25 lbs.)/12.5kg (27.56 lbs.) |
| Internal Cable Management Depth | 32mm |
| Power Supply | ATX PSU |

## Warranty

2 years

## Features

1. Comes equipped with a full tempered glass side panel and front panel
2. Comes equipped with three 14cm Edge Addressable RGB fans in the front panel and one 14cm Edge Addressable RGB fan in the rear
3. Addressable RGB fans can be controlled using one of three ways:
   - RGB LED control button on top of the case
   - Convenient RGB remote control
   - Addressable RGB motherboard
4. Supports E-ATX motherboards for maximum performance
5. Supports liquid cooling:
   - Front: 480mm Radiator (Optional)
   - Rear: 240mm/280mm Radiator (Optional)
   - Bottom: 240mm/280mm Radiator (Optional)
   - PSU: 360mm Radiator (Optional)
6. Maximum air-cooling support with up to 12 fans:
   - Front: 120mm x 4 or 140mm x 3 or 200mm x 2 (Includes 140mm RGB Fans x 3)
   - Rear: 120mm x 2 or 140mm x 2 (Includes 140mm RGB Fan x 1)
   - Bottom: 120mm x 3 or 140mm x 2 (Optional)
   - PSU: 120mm x 3 or 140mm x 2 (Optional)
7. Supports CPU cooler up to 189mm
8. Supports high-end graphics cards up to 383mm
9. Supports up to 2 x 3.5” HDDs and 2 x 2.5” SSDs

## Package Information

| Model Name | Model No. | EAN CODE | UPC CODE |
|---|---|---|---|
| Tor Pro-G-BK-v1 | ACCF-PB11043.11 | 4718009156937 | |
| | | | |

| Carton Size (L x W x H) | 610 x 315 x 570 mm (3.87 CuFt) | |
|---|---|---|
| Pallet Size (L x W x H) | 1000 x 1200 x 120mm | |
| Container | w/ Pallet | w/o Pallet |
| 20’ | 18 X 10 | 252 |
| 40’ | 18 X 20 | 532 |
| 40’ HQ | 20 X 20 | 608 |