WHU629EW/S

Classic undertable cooker hood



LedLight

Re-circulating hoods

Noise level

Useful tips

What capacity do you need?

Undertable cooker hood
Venting with air extraction or recirculation
Energy class: **B**
Material of housing/chimney: **varnished steel**
Colour of housing/chimney: **White**

Lightning efficiency class: **B**
Grease filtering efficiency class: **C**
Fluid dynamic efficiency class: **E**
Maximum extraction rate by extraction operation: **200 m³/h**
Maximum extraction rate by recirculation operation: **115 m³/h**
Venting tube diameter: **12 cm**

Air flow by extraction version, step 1: **108 m³/h**
Air flow by extraction version, step 2: **159 m³/h**
Air flow by extraction version, step 3: **200 m³/h**

Mechanic control
Number of speed positions: **3**

Lamp type: **LED**
On/off light switch
Number of lights: **1**
Power of lights: **4 W**

Filter material: **Syntetic**
Coal filter code (optional as separate purchase): **784407**
Washable grease filter
Number of motors: **1**
No return airflow flap: **125 mm**

Max. noise level: **64 dB(A)re 1 pW**
Height: **125 mm**
Annual energy consumption : **29.1 kWh**
Dimensions (W×H×D): **59.6 × 12.5 × 46.8 cm**
Dimensions of packed product (W×H×D): **64.6 × 17.8 × 52.4 cm**
Net weight: **4.8 kg**
Gross weight: **5.49 kg**
Nominal current of fuse: **10 amp**
Product code: **733030**
EAN code: **3838782171550**

http://tn.gorenje.com/en/product/733030