# Vertiv™ Geist™ rPDU

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.




## Part #: 28141

**Model Number:** NSVKN080-102S20TL
**Category:** Basic
**Sub Category:** Standard
**Power Configuration:** 20A, 120V, 1.9kW
**Physical Configuration:** 24in / 610mm, Vertical

**Product Summary:** rPDU, Basic Standard, 20A, 120V, 1.9kW, Vertical, (8) NEMA 5-20R, 10ft power cord with L5-20P, Black Powder Coat.

**Plug Form:**



L5-20P

**Receptacle:**



NEMA 5-20R
(Quantity: 8)

**Chassis Color Options:**



*To discuss color options, contact your local sales representative.*

## Product Specification and Options

**System Features**

| | |
|---|---|
| Quantity Of Inputs | 1 |
| Voltage | 100-120V |
| Current | 20A |
| VA per Input (Load Capacity) | 1.9kW (120V) |
| Frequency | 50/60Hz |


© Vertiv Group Corp. All rights reserved. Vertiv™, and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.

| | |
|---|---|
| **Over Current Protection** | 20A Thermal Breaker |
| **Switch** | No |
| **Indicators - LED(s)** | 1 - Power ON Green LED |
| **Power Cable Wire Gauge** | 12/3 |
| **Power Cable Length** | 10ft |
| **Plug Type** | NEMA L5-20P Twistlock |
| **Receptacle/Socket Type #1** | NEMA 5-20R |
| **- Quantity on Face** | 8 |
| **- Quantity per Breaker** | 8 |
| **- Style** | Individual - In-Line |
| **- Maximum Output per Receptacle/Socket** | 20A |
| **- Voltage per Receptacle/Socket** | 120V |
| **Center to Center Receptacle Spacing** | 2.0 |
| **Continuous Operating Temperature Range** | 10-45C / 50-113F |
| **Heavy Steel - Powder Coat Finish** | Black |
| **Configuration** | 24in / 600mm Vertical Rackmount |
| **Plastic Mounting Clips** | 1 - Bottom; 1 - Top |
| **Country of Origin** | USA, TAA Compliant and Buy American Act COTS Compliant |
| **Product Warranty** | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| **Certification/Agency Approvals** | RoHS Compliant |
| **Certification/Agency Approvals** | UL & c-UL Listed 60950 |
| **Chassis Dimensions (LxWxD)** | 24.00in x 1.61in x 1.61in |
| **Shipped Weight** | 5lbs (2.27kg) |


© Vertiv Group Corp. All rights reserved. Vertiv™, and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.