# Vertiv™ Geist™ rPDU

## OVERVIEW

Metered rPDUs deliver reliable power to critical IT equipment within a rack or cabinet. Includes a local LED display to view real-time power data.

### Benefits

- Avoid accidental overloads when deploying or moving critical server equipment with instant access to power consumption metrics on the local digital display.
- The local LED display provides real-time power data for instant feedback when deploying or moving critical IT equipment.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.




## Part #: 13192

**Model Number:** VHVLAN102-102C13TL6
**Category:** Metered
**Sub Category:** Standard
**Power Configuration:** 20A, 208V, 3.3kW
**Physical Configuration:** 17in / 432mm, Horizontal/Vertical

**Product Summary:** rPDU, Metered Standard, 20A, 208V, 3.3kW, Horizontal/Vertical, (10) IEC C13, 10ft power cord with L6-20P, Black Powder Coat.

**Monitoring:** Current - Local

Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input

**Plug Form:**



L6-20P

**Receptacle:**



IEC C13
(Quantity: 10)

**Chassis Color Options:**



*To discuss color options, contact your local sales representative.*

## Product Specification and Options

**System Features**


© Vertiv Group Corp. All rights reserved. Vertiv™, and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.

| | |
|---|---|
| **Monitoring** | Current - Local<br><br>Digital RMS Current Meter +/- 2% Accuracy with Full Scale 60Hz sine wave input |
| **Monitoring Level 1** | Aggregate - Total Unit Monitoring |
| **Quantity Of Inputs** | 1 |
| **Voltage** | 200-240V |
| **Current** | 20A |
| **VA per Input (Load Capacity)** | 3.3kW (208V) |
| **Frequency** | 50/60Hz |
| **Over Current Protection** | None |
| **Switch** | No |
| **Power Cable Wire Gauge** | 12/3 |
| **Power Cable Length** | 10ft |
| **Plug Type** | NEMA L6-20P Twistlock |
| **Receptacle/Socket Type #1** | IEC C13 |
| **- Quantity on Face** | 10 |
| **- Style** | Banks of 5 |
| **- Maximum Output per Receptacle/Socket** | 15A per receptacle bank |
| **- Voltage per Receptacle/Socket** | 208V |
| **Continuous Operating Temperature Range** | 10-45C / 50-113F |
| **Heavy Steel - Powder Coat Finish** | Black |
| **Configuration** | 17in / 432mm Vertical/Horizontal Rackmount |
| **19in Panel Mount Brackets** | Yes |
| **SLB-4 Brackets** | Yes |
| **Country of Origin** | USA, TAA Compliant and Buy American Act COTS Compliant |
| **Product Warranty** | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| **Certification/Agency Approvals** | RoHS Compliant |
| **Certification/Agency Approvals** | UL & c-UL Listed 60950 |
| **Chassis Dimensions (LxWxD)** | 17.00in x 1.72in x 1.61in |
| **Shipped Weight** | 6lbs (2.72kg) |


© Vertiv Group Corp. All rights reserved. Vertiv™, and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.