# Vertiv™ Geist™ rPDU

## OVERVIEW

Basic surge protected rPDUs deliver reliable power to critical IT equipment within a rack or cabinet and comes equipped with built-in surge protection.

### Benefits

- Ideal for environments lacking facility-level surge suppression or for applications requiring additional protection.
- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.




## Part #: 29420

**Model Number:** SP064-10
**Category:** Basic
**Sub Category:** Surge
**Power Configuration:** 15A, 120V, 1.4kW
**Physical Configuration:** 19in / 483mm, Horizontal

**Product Summary:** rPDU, Basic Surge, 15A, 120V, 1.4kW, Horizontal, (6) NEMA 5-15R, 10ft power cord with 5-15P, Black Powder Coat.

**Plug Form:**



5-15P

**Receptacle:**



NEMA 5-15R
(Quantity: 6)

**Chassis Color Options:**



*To discuss color options, contact your local sales representative.*

## Product Specification and Options

**System Features**

| | |
|---|---|
| **Quantity Of Inputs** | 1 |


© Vertiv Group Corp. All rights reserved. Vertiv™, and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.

| | |
|---|---|
| **Voltage** | 100-120V |
| **Current** | 15A |
| **VA per Input (Load Capacity)** | 1.4kW (120V) |
| **Frequency** | 50/60Hz |
| **Over Current Protection** | 15A Thermal Breaker |
| **Switch** | Yes |
| **Indicators - LED(s)** | 1 - Power ON Green LED |
| **Power Cable Wire Gauge** | 14/3 |
| **Power Cable Length** | 10ft |
| **Plug Type** | NEMA 5-15P |
| **Receptacle/Socket Type #1** | NEMA 5-15R |
| **- Quantity on Rear** | 6 |
| **- Quantity per Breaker** | 6 |
| **- Style** | Duplex |
| **- Maximum Output per Receptacle/Socket** | 15A |
| **- Voltage per Receptacle/Socket** | 120V |
| **Joule Rating** | 720 |
| **Maximum Clamping Voltage** | 340V |
| **Response Time** | < 5 nanoseconds |
| **Technology Used** | Super MOVS |
| **Surge Indicator Red LED** | Yes |
| **Continuous Operating Temperature Range** | 10-45C / 50-113F |
| **Heavy Steel - Powder Coat Finish** | Black |
| **Configuration** | 19in / 483mm Horizontal Rackmount |
| **Flush Mount** | Yes |
| **Country of Origin** | USA, TAA Compliant and Buy American Act COTS Compliant |
| **Product Warranty** | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| **Connected Equipment Warranty** | 5 years / $5,000 |
| **Certification/Agency Approvals** | RoHS Compliant |
| **Certification/Agency Approvals** | UL & c-UL Listed 60950 |
| **Chassis Dimensions (HxWxD)** | 1.72in x 17in x 3.75in |
| **Shipped Weight** | 6lbs (2.72kg) |


© Vertiv Group Corp. All rights reserved. Vertiv™, and the Vertiv logo are trademarks or registered trademarks of Vertiv Group Corp. All other names and logos referred to are trade names, trademarks or registered trademarks of their respective owners. While every precaution has been taken to ensure accuracy and completeness here, Vertiv Group Corp. assumes no responsibility, and disclaims all liability, for damages resulting from use of this information or for any errors or omissions. Specifications, rebates and other promotional offers are subject to change at Vertiv's sole discretion upon notice.