Swordfish

15 Inches Full Flat Fanless POS System

The Capture Swordfish is a space saving full flat touch screen POS terminal that suit for variety of market segments.

The Swordfish consists of low power consumption processors and fanless cooling technology to enable the Swordfish operate with less noise and heat; that makes Swordfish suitable for the location that noise is often taken into consideration.

Multi-Functional, space saving, Noise-Free and efficient. The Swordfish is your ideal choice of Point of Sale system.

Functional all-in-one capacitive touch POS terminal

Swordfish offers a smart and cost-effective design which falls within the price range of almost every price-cautious customer and capable enough for most of the POS application needs. Its enclosure is constructed with the top quality die-cast metal, and a sleek stand that can effectively save the limited counter space.

Equipped with an eye-friendly 15-inch LCD with resistive touch and built-in Intel Celeron J1900 Quad Core 2.0G Processor with 8GB DDR3L Memory, plenty I/O ports for POS peripherals, and the cost-effective Windows IOT Enterprise Operating System features are efficient for most of the everyday tasks for a POS terminal.

- Bay Trail Celeron J1900 (2.0 GHz).
- 8GB DDR3L RAM module.
- 128GB SSD HDD.
- 15 inch Full-Flat LCD monitor.
- Touch Screen: Projective Capacitive (Multi-Touch support).
- Fanless Cooling System.
- Gigabit LAN Port.
- Versatile I/O support: USB 3.0 / USB 2.0 / RS-232 / RJ-11 / RJ-45...etc.
- Compact Base Design Ideal for Small Workplace Operation.



capture

System

CPU	Intel® Bay Trail-D Platform, Celeron® Processor J1900 (2.0 GHz, 2M Cache, up to 2.42 GHz)
System Memory	8GB DDR3L SO-DIMM 1333MHz
Graphic	Intel® HD Graphics
OS Support	Windows 10 IoT

Display

Screen Size	15"
Brightness	300 nits
Resolution	1024 x 768 Pixel
Touch Screen	Projective Capacitive
Tilting Angle	15° ~ 85°

Storage

HDD	128GB SSD
Auxiliary Storage	1 x mSATA slot (Internal)

Interface

Serial	4 x COM (DB9, with power output, +5VDC/+12VDC, selectable by Jumper)
	2 x COM (Internal, reserved for VFD Customer Display and MSR)
Parallel	1 x DB25 Parallel Port
USB	5 x USB 2.0 (External, 4 x bottom/ 1 x side)
LAN	1 x RJ-45, Giga LAN Support
VGA	1 x DB-15, Female
DC Out	1 x 12VDC Jack for Customer Display or 2nd Display
Cash Drawer	1 x RJ-11, +12/+24 VDC
Audio	1 x Internal Speaker

Safety & Regulatory

Compliance	FCC / CE / WEEE / RoHS

General

Product dimensions	303 mm (H) x 355 mm (W) 205 mm (D)
Package dimensions	410 mm (H) x 290 mm (W) 480 mm (D)
Weight net/gross	5 kg / 7 kg
Color	Black
Power Adaptor	+12VDC 60W,4-pin Connector with Lock (External Adaptor: 100 ~ 240 VAC, 50/60HZ)
Operating Temperature	0°C ~ 40°C
Operating Humidity	20% ~ 80% RH non-condensing
Storage Temperature	-20°C ~ 55°C
Storage Humidity	20% ~ 85% RH non-condensing

Item

Item no.	CA-SY-10122
EAN:	5706998572219
QTY in carton	1

capture