Group hood 54 cm Group

DGE5661HM



Power of invisibility
The most discreet of kitchen hoods, it is designed with integrated Hob2Hood connectivity. The hands-free system allows the hob to communicate with the hood, intuitively managing the air ventilation and lighting in the cooking area. All without being seen.

The most discreet of kitchen hoods, it is designed with integrated Hob2Hood connectivity. The hands-free system allows the hob to communicate with the hood, intuitively managing the air ventilation and lighting in the cooking area. All without being seen.

Product Benefits & Features



The hands-free hood
This cooker hood has Hob2Hood, a useful feature that automatically controls your cooker hood and lights. Leave Hob2Hood to regulate the fan while you concentrate on the key moments involved in getting your dish just right. But if you'd rather adjust the fan speed yourself, there are manual controls on the cooker hood too.



Clean air with less energy
A strong motor with low-energy consumption means this hood is reliable and efficienty clears away kitchen odours.



Clean air. Faster.
This Cooker hood clears the kitchen from cooking fumes quickly. That is beacuse the advanced cooker hood has an effecient and powerful motor.

One touch. Complete control
The full range of hood functions are consolidated into a single electronic control. Meaning settings can be monitored and adjusted with just one touch. Precisely and intuitively.

- Electronic variable 3+Intensive speed push button control
- Washable aluminium grease filters
- Extraction mode
- Recirculation or extraction options
- For installation into an island chimney or corner unit

AEG

Group hood 54 cm Group

DGE5661HM

Product Specification

Installation	Group	No. of lamps	2
Size	54	Grease filters	1
Dimensions, HxWxD	-331x540x300	Recirc sound power min, dB(A)	62
Minimum distance from cooking top	50	Recirc sound power max, dB(A)	74
Minimum distance from cooking top	57	Recirculation min, m3/h	295
Cord Length	1.8	Recirculation max, m3/h	430
Voltage	220-240		
Required Fuse	No		
Frequency	50		
Colour	Stainless steel		
Charcoal filter type	ECFB01		
Superperforming charcoal filter compatible	NO, NO		
Energy class	A		
Fluid dynamic efficiency class	A		
Lighting efficiency class	A		
Grease filter efficiency class	D		
Capacity minimum, m3/h	300		
Capacity, Max m³/h	580		
Capacity intensive, m3/h	700		
Sound power min speed, dB(A)	54		
Sound power max speed, dB(A)	67		
Sound power intensive, dB(A)	70		
No. of speed settings	3+Intensive		
Lamp type	LED spotlight		

