PHILIPS

Lighting



GreenSpace

DN470B LED20S/840 PSE-E C WH GC

GreenSpace Compact UGR22 - LED Module, system flux 2000 lm - 840 neutral white - Power supply unit external, DC compatible for central emergency lighting - Wire-protected, splash-proof - White

Customers want to strike the ideal balance between their initial investment and the cost of the installation during its lifetime. GreenSpace is a cost-efficient and sustainable downlight that can be used to replace conventional CFL downlights in general lighting applications. It features the latest LED technology, which enables extremely low power consumption, while delivering consistent light output, stable color performance and high color rendering. The product's long lifetime makes it a true 'fit and forget' solution.

Product data

General Information	
Number of light sources	1 [1 pc]
Lamp family code	LED20S [LED Module, system flux 2000 lm]
Beam angle of light source	120 °
Light source colour	840 neutral white
Cap base	- [-]
Light source replaceable	No
Number of gear units	1 unit
Gear	-
Driver/power unit/transformer	PSE-E [Power supply unit external, DC compatible for central emergency lighting]
Driver included	Yes
Optic type	C [High-gloss mirror]
Luminaire light beam spread	88°

Emergency lighting	No [-]
Connection	Push-in connector and pull relief
Cable	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 850 °C, duration 5 s
Flammability mark	F [For mounting on normally flammable surfaces]
CE mark	CE mark
ENEC mark	ENEC mark
Warranty period	5 years
Remarks	*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance

	between B50 and for example B10. Therefore the median useful life (B50) value also represents the B10 value.
Constant light output	No
Number of products on MCB	30
RoHS mark	RoHS mark
Product Family Code	DN470B [GreenSpace Compact UGR22]
Unified glare rating CEN	22

Light Technical

Optical cover/lens type accessory	GC [Glass cover clear]

Operating and Electrical

Electrical accessories	No [-]
Input voltage	220 to 240 V
Input frequency	50 to 60 Hz
Inrush current	14 A
Inrush time	0.24 ms
Power factor (min.)	0.9

Controls and Dimming

Dimmable	No

Mechanical and Housing

Housing material	Aluminium
Reflector material	Polycarbonate aluminium coated
Optic material	Polycarbonate
Optical cover/lens material	Glass
Fixation material	-
Optical cover/lens finish	Clear
Overall height	95 mm
Overall diameter	216 mm
Colour	White

Approval and Application

Ingress protection code	IP44 [Wire-protected, splash-proof]
Mech. impact protection code	IK02 [0.2 J standard]

Initial Performance (IEC Compliant)

Initial luminous flux	2200 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	118.28 lm/W
Init. Corr. colour temperature	4000 K
Init. colour rendering index	80
Initial chromaticity	(0.38, 0.38) SDCM <5
Initial input power	18.6 W
Power consumption tolerance	+/-5%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L80

Application Conditions

Ambient temperature range	+10 to +40 °C
Performance ambient temperature Tq	25 °C
Suitable for random switching	Yes (relates to presence/ movement detection and daylight harvesting)

Product Data

Full product code	871869624340400
Order product name	DN470B LED20S/840 PSE-E C WH GC
EAN/UPC – product	8718696243404
Order code	24340400
Numerator – quantity per pack	1
Numerator – packs per outer box	1
Material no. (12NC)	910500454969
Net weight (piece)	1.140 kg

Dimensional drawing



GreenSpace gen2 DN460B-DN473B

GreenSpace

Photometric data



IFGU1_DN470BIP441xLED20S840C



IFPC1_DN470BIP441xLED20S840C

© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.