GRAPHICS CARD

GeForce RTX 2080 SUPER™ AERO







SPECIFICATION

Model Name	GeForce® RTX 2080 SUPER™ AERO
Graphics Processing Unit	NVIDIA® GeForce RTX™ 2080 SUPER
Interface	PCI Express x16 3.0
Cores	3072 Units
Core Clocks	Boost: 1815 MHz
Memory Speed	15.5 Gbps
Memory	8GB GDDR6
Memory Bus	256-bit
Output	DisplayPort x 3 (v1.4) / HDMI 2.0b x 1
HDCP Support	2.2
Power consumption	250 W
Power connectors	8-pin x 1, 6-pin x 1
Recommended PSU	650 W
Card Dimension(mm)	265 x 114 x 40 mm
Weight (Card / Package)	862 g / 1554 g
Afterburner OC	Y
DirectX Version Support	12 API
OpenGL Version Support	4.5
Multi-GPU Technology	NVIDIA® NVLink™ (SLI-Ready), 2-way
Maximum Displays	4
VR Ready	Y
G-SYNC® technology	Y
Adaptive Vertical Sync	Y
Digital Maximum Resolution	7680x4320

CONNECTIONS



1. DisplayPort
2. HDMI

FEATURE

PREMIUM DESIGN

MSI AERO graphics cards are equipped with a sleek, but neutral design, crafted from premium materials.

VR Ready

Certified to provide the performance required for a smooth experience in your VR adventures.

MSI Afterburner

The ultimate overclocking software with advanced control options and real-time hardware monitor.

MULTI GPU SUPPORT

MSI graphics cards fully support multi-GPU setups using NVIDIA® SLI® technology on eligible GPU's.

NVIDIA® G-SYNC®

Gives you more of what you want in a gaming experience. Incredibly smooth, tear-free gameplay at refresh rates up to 240 Hz.

SOLID BLACK & RED BACKPLATE

Increases toughness of the card to prevent bending while complementing the sleek MSI design.

Generated 2019-11-12, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2018 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved. © 2016 NVIDIA, the NVIDIA logo, GeForce, SHIELD, and NVIDIA G-SYNC are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries.