ThinkStation P520c 30BX004LPG

Product
ThinkStation P520c

Region
WE

Country/Region
Portugal

Machine Type
30BX

TopSeller
TopSeller

Processor
Xeon W-2123 4C/8T/3.6GHz/8.25MB/120W/DDR4-2666

Memory
1x 16GB RDIMM DDR4-2666 ECC

Discrete Graphics Card
None

Monitor Cable
None

Storage Controller
Onboard Intel SATA RSTe Controller

M.2 SSD RAID Controller
RAID 0/1/10 Upgrade

Internal Disk
None

M.2 SSD Drive
1x 512GB SSD M.2 PCIe NVMe Opal

PCIe SSD Adapter
None

Optical
1x HH DVD±RW

Media Reader
SD Reader

HD Audio
Onboard Realtek ALC662

WLAN + Bluetooth
None

Available Networking Port
1x GbE RJ-45

Chassis Intrusion Switch
Chassis Intrusion Switch

Cover Lock
None

Optional 1394 Port
None

Optional Parallel Port
None

Optional Thunderbolt Port
None

Optional Serial Port
1x Serial

Optional USB Port
None

Optional eSATA Port
None

Keyboard
USB Traditional Keyboard

Mouse
USB Calliope Mouse

Power Supply
Fixed 500W Platinum

Diagnostic
None

System Management
Intel AMT 11

Operating System
Windows 10 Pro 64 for Workstations

Bundled Software
None

Base Warranty
3-year, Onsite

Upsell Service Bundles
None

Global
No

End of Support
2024-05-03

Announce Date
2018-04-03

WWW.LENOVO.COM

This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifcations or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication “as is” without warranty of any kind, either express or implied, including the implied warranties of merchantability or ftness for a particular purpose.

http://psref.lenovo.com

Visit psref website for the latest version of Product Specifcations Reference.

© Lenovo, 2019. All rights reserved.



ThinkStation P520c Platform Specifications

Form factor	25L Tower
Dimensions	175mm/6.89" W x 426mm/16.77" D x 376mm/14.8" H (with feet)
Weight	Maximum configuration: 31.97 lb (14.5kg)
Processor Family	Up to one 140W Intel Xeon W family processor: • Up to 18 cores at 2.3 GHz • Up to 4.0 GHz with 4 cores • Up to 24.75 MB cache • Up to DDR4-2666 memory speed
Processor Sockets	1x FCLGA2066
Chipset	Intel C422 Chipset
Memory Sockets	4 DIMM sockets with 4 channels
Memory Types	DDR4-2666 RDIMM
Memory Capacity	128GB with 4 x 32GB RDIMMs
Memory Protection	ECC
Expansion slots	Slot 1 (CPU) PCIe 3.0 x16, full height, full length, 75W, Slot 2 (CPU) PCIe 3.0 x8, full height, full length, 25W, open ended Slot 3 (CPU) PCIe 3.0 x16, full height, full length, 75W Slot 4 (PCH) PCIe 3.0 x4, full height, half length, 25W, open ended

Discrete Graphics Offering

Graphics	Memory	Power	Connector	SLI / NVlink	Max Qty
NVS 810	4GB DDR3	68W	8xmini DP		1
Quadro P400	2GB GDDR5	30W	3xminiDP		2
Quadro P600	2GB GDDR5	45W	4xminiDP		2
Quadro P620	2GB GDDR5	40W	4x miniDP		2
Quadro P1000	4GB GDDR5	50W	4xminiDP		2
Quadro P2000	5GB GDDR5	75W	4xDP		2
Quadro P4000	8GB GDDR5	120W	4xDP		2
Quadro P5000	16GB GDDR5X	180W	DVI-D DL+4xDP		1
Quadro RTX 4000	8GB GDDR6	160W	3xDP, 1xVirtualLink		1

Storage Controller

Storage Controller	Type	Interface	RAID	Cache
Onboard Intel RSTe	Std	SATA 6Gb/s	0/1/10/5	
9440-8i PCIe	Opt	SAS 12Gb/s, SATA 6Gb/s	0/1/10/5	
NVMe Basic	Opt	PCIe NVMe	0/1/10	
NVMe for Intel SSD	Opt	PCIe NVMe	0/1/10/5	

Storage Support

Disk Type	Interface	RPM	Offering	Max Qty
3.5" SATA HDD	SATA 6Gb/s	7.2K	1TB/2TB/4TB/6TB	4
2.5" SATA HDD	SATA 6Gb/s	7.2K	500GB/500GB FIPS	4
2.5" SATA SSD	SATA 6Gb/s		256GB/512GB/1TB/2TB	4
M.2 PCIe SSD	PCIe NVMe		256GB/512GB/1TB/2TB	5

Storage Bays

Bay Type	Maximum Drives Qty
M.2 slot	5x M.2 SSD (2 onboard, 3 via PCIe to M.2 adapter)
Flex Bay	2 flex bays. Supports the following: • 2x half-height optical drives • 2x 5.25" 9.0mm optical drives • 1x 5.25" 9.0mm optical drive + 2x 3.5"/2.5" SATA SSD/HDD • 1x 3.5"/2.5" SATA SSD/HDD with Front Access Storage Enclosure • 1x flex module for the following options: Tray 1: 9.0mm optical Tray 2: 15-in-1 USB 3.0 reader, 2x Thunderbolt, or 4-digit diagnostic display Port 1 and 2: Front USB 3.0 Type-C or eSATA • 2x M.2 SSD with 2x Front Removable Drive Enclosures
Disk bay	Up to 2x 3.5"/2.5" disks with 2 disk bays

Max Storage	Supports up to 5x M.2 SSD + 4x 3.5" HDD/4x 2.5" SSD/4x 2.5" HDD All HDD: 24TB using 4x 3.5" HDD All SSD: 18TB using 4x 2.5" SATA SSD and 5x M.2 SSD
Power supply	One fixed 500W, autosensing, 92%, 80 PLUS Platinum qualified
Media reader	SD USB 2.0 card reader on most models. Optional UHS-II 15-in-1 USB 3.0 reader on flex module
Network interfaces	Integrated one gigabit ethernet (Intel i219LM), supports Wake-on-LAN. Optional PCIe ethernet or wireless adapters are available
WLAN + Bluetooth	Optional Intel Wireless-AC 8265, 2x2, 2.4GHz/5GHz, 802.11ac, Bluetooth 4.2, up to 867Mbps
Security features	Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant, switch to 1.2 via UEFI setting. Optional access panel lock, Kensington lock, and pad lock
Intel vPro	Intel vPro technology supported. vPro requires Wireless-AC 8265 if Wi-Fi is needed
Intel AMT	Intel Active Management Technology 11
Diagnostic	ThinkStation Diagnostics for Windows. Optional front 4-digit diagnostic display on flex module
Base warranty	1 or 3-year limited onsite service with 9x5/NBD
HD Audio	Realtek ALC662 codec
Front ports	2x USB 3.0, microphone (3.5mm), headphone (3.5mm)
Rear ports	2x USB 2.0, 4x USB 3.0, 1x RJ-45, 3x analog audio ports (line-in, line-out, mic-in), 2x PS/2
Optional ports	Supports the following optional ports: Front: • 2x Thunderbolt ports (USB Type-C) on flex module, one of two ports supports video-out • 1x eSATA on flex module • 1x USB Type-C on flex module, USB 3.1 gen 1 Rear: • 1x COM port • 2x USB Type-C ports via PCIe adapter, USB 3.1 gen 2. One 15W, one 5W Internal: • 1x internal USB 3.0 port

Environmental specification

Temperature - operating	50 °F to 95 °F (10 °C to 35 °C)
Temperature - storage (no package)	14 °F to 140 °F (-10 °C to 60 °C)
Temperature - storage (with package)	-40 °F to 140 °F (-40 °C to 60 °C)
Altitude - operating	(Unpressurized): -50ft-10000ft (-15.2m-3048m)
Humidity - operating	10%~80%, non-condensing
Humidity - storage (with package)	10%~90%, non-condensing

Environmental Certifications	RoHS-compliant. GREENGUARD. EPEAT Silver rating. ENERGY STAR 6.1 qualified on model 30BX0008US and 30BX0009US
ISV certifications	Please visit www.thinkworkstations.com/isv-certifications/

Note:
1. Depending on many factors, actual data transfer speed mentioned on this page may be lower than theoretical speed.
2. Any questions or advice on ThinkStation PSREF, please contact ThinkStation PSREF developer

ThinkStation P520c









