SAMSUNG

FJM Technical Data Book

Free Joint Multi for Europe (R32, 50Hz, HP)



Model : Outdoor unit (AJ***NCJ2EG/EU)
Indoor unit (AR**NXWSAURNEU, AR**MXWSAWKNEU, AR**NXFPEWQNEU, AR**NXFHBWKNEU, AR**NXWXCWKNEU, AR**NXPXBWKNEU, AR**NXWXBWKNEU, AR**NXCXAWKNEU)

2. Specification

2-2. Indoor units

Wall Mounted Type - Maldives

Type				Maldives	Maldives	Maldives
Model Name				AR07NXFPEWQNEU	AR09NXFPEWQNEU	AR12NXFPEWQNEU
Power Supply			Φ, #, V, Hz	1, 2, 220~240, 50	1, 2, 220~240, 50	1, 2, 220~240, 50
Mode			-	HP	HP	HP
Performance	Capacity	Cooling	kW	2.0	2.75	3.5
			Btu/h	6,800	9,400	11,900
		Heating	kW	2.2	3.2	3.5
			Btu/h	7,500	10,900	11,900
Power	Power Input	Cooling	W	30	30	30
		Heating		30	30	30
	Current Input	Cooling	A	0.3	0.3	0.3
		Heating		0.3	0.3	0.3
Heat exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
	Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile
Fan	Type		-	Cross flow Fan	Cross flow Fan	Cross flow Fan
	Quantity		EA	1	1	1
	Air Flow Rate		m^3/min	8.0	9.0	10.0
			l/s	133.3	150.0	166.7
	External Static pressure	Max. (Min/Std/Max)	mmAq	-	-	-
			Pa	-	-	-
Fan Motor	Type		-	BLDC Motor	BLDC Motor	BLDC Motor
	Output x n		W	27 x 1	27 x 1	27 x 1
Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")
	Gas Pipe		Type	Flare connection	Flare connection	Flare connection
			Φ, mm (inch)	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")
	Heat Insulation		-	Both Liquid & Gas pipes	Both Liquid & Gas pipes	Both Liquid & Gas pipes
	Drain Pipe		Φ,mm	ID 18mm Hose	ID 18mm Hose	ID 18mm Hose
Wiring connections	Communication	Min.	mm^2	0.75	0.75	0.75
		Remark	-	F1, F2	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32	R32
	Electronic Expansion Valve		-	EEV NOT INCLUDED	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	H/M/L	dB(A)	38 / 28 / 21	38 / 28 / 21	42 / 33 / 23
	Sound Power	Cooling		56	56	59
Dimensions	Net Weight		kg	8.0	8.0	8.0
	Shipping Weight		kg	9.7	9.7	9.7
	Net Dimensions (WxHxD)		mm	820 x 285 x 215	820 x 285 x 215	820 x 285 x 215
	Shipping Dimensions (WxHxD)		mm	880 x 260 x 360	880 x 260 x 360	880 x 260 x 360
Casing	Material		-	HIPS	HIPS	HIPS

NOTE

- Specifications may be subject to change without prior notice.
- 1)* Capacities are based on (Equivalent refrigerant piping : 5m, Level differences : 0m)
  - Cooling : Indoor temperature : 27°C DB, 19°C WB / Outdoor temperature : 35°C DB, 24°C WB
  - Heating : Indoor temperature : 20°C DB, 15°C WB / Outdoor temperature : 7°C DB, 6°C WB
- 2)* Select wire size based on the value of MCA
- 3)* Sound pressure level is obtained in an anechoic room.
  - Sound pressure level is a relative value, depending on the distance and acoustic environment.
  - Sound pressure level may differ depending on operation condition.
  - dBA = A-weighted sound pressure level
  - Reference acoustic pressure 0 dB = 20uPa
- 4)* Sound power level is an absolute value that a sound source generates.
  - dBA = A-weighted sound power level
  - Reference power : 1pW
  - Measured according to ISO 3741
- 5)* These products contain R32 (GWP=675) which is fluorinated greenhouse gas.