MPN: 0070-25452

Corona IP-452 IR Bullet

Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Form factor: Bullet, Mounting type: Ceiling/Wall, Product colour: Black,White. Minimum illumination: 0.002 lx, Angle of rotation: 360°, Viewing angle, horizontal: 103.3°. Sensor type: CMOS, Optical sensor size: 25.4 / 1.8 mm (1 / 1.8"). Focus: Motorized/Manual, Focal length range (f-f): 2.8 - 12 mm



- 1/1.8” Progressive Scan CMOS
- 1920 × 1080 @ 60fps
- Color: 0.002 Lux @ (F1.2, AGC ON)
- H.265, H.265+, H.264+, H.264
- 140dB WDR
- 3D DNR
- 6 behavior analyses, 3 exception detections, face detection, and counting
- 5 defined streams and up to 5 custom streams supported
- On-board storage up to 256 GB
- IP67,IK10

Specifications

Camera	**Angle of rotation**	360 °
	Camera pan control	No
	Camera shutter speed	1 - 1/100000 s
	Minimum illumination	0.002 lx
	Pan range	0 - 355 °
	Tilt angle range	0 - 90 °
	Viewing angle, diagonal	124.2 °
	Viewing angle, horizontal	103.3 °
	Viewing angle, vertical	54.2 °
	White balance	Manual
Design	**Form factor**	Bullet
	IK code	IK10
	International Protection (IP) code	IP67
	Mounting type	Ceiling/wall
	Product colour	White
Features	**NDAA Compliance**	Yes
Image sensor	**Optical sensor size**	1/1.8 "
	Progressive scan	Yes
	Sensor type	CMOS
Lens system	**Auto focus**	Yes
	Focal length range	2.8 - 12 mm
	Focus	Motorized/Manual
	Maximum aperture number	1.2

Management features	**Behavior analysis**	Intrusion detection, Line crossing detection, Object removal detection, Region entrance detection, Region exiting detection, Unattended baggage detection
	Web browser	Yes
	Web-based management	Yes
Network	**3G**	No
	4G	No
	Bluetooth	No
	Cabling technology	10/100/1000BaseT(X)
	Ethernet interface type	Gigabit Ethernet
	Ethernet LAN	Yes
	Networking standards	IEEE 802.1x
	Number of users	32 user(s)
	Quality of Service (QoS) support	Yes
	Supported network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
	Wi-Fi	No
Night vision	**Infra-red wavelength**	850 nm
	LED type	IR
	Night vision	Yes
	Night vision distance	50 m
Operational conditions	**Operating relative humidity (H-H)**	0 - 95 %
	Operating temperature (T-T)	-30 - 60 °C
Packaging content	**Number of cameras**	1
Performance	**Alarm input/output**	Yes
	Connectivity technology	Wired
	Day/night mode	Yes
	Infrared (IR) cut-off filter	Yes
	Placement supported	Indoor & outdoor
	Type	IP security camera
	Wide Dynamic Range (WDR)	Yes
Ports & interfaces	**BNC output ports**	1
	Composite video out	1
	Interface	RJ45
Power	**DC output current**	1 A
	DC output voltage	12
	Power consumption (max)	12 W
	Power source type	DC, PoE
Security	**Digital watermark**	Yes
	Heartbeat	Yes

Security	**Intelligent Video Surveillance (IVS) system features**	Face detection, Defocus, Scene change
	IP address filtering	Yes
	Password protection	Yes
	Video motion detection	Yes
Storage	**Built-in HDD**	No
	Built-in SSD	No
	Card reader integrated	Yes
	Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
	Maximum memory card size	256 GB
Vendor information	**Brand Name**	Ernitec
	Homepage	http://www.ernitec.com
	Warranty	3 Year(s)
Video	**3D NR (Noise Reduction)**	Yes
	Automatic gain control	Yes
	Back Light Compensation (BLC)	Yes
	Frame rate	60 fps
	Full HD	Yes
	Highlight Compensation (HLC)	Yes
	Image quality adjustment	Brightness, Contrast, Saturation, Sharpness
	Maximum resolution	1920 x 1080 pixels
	Supported graphics resolutions	640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
	Total megapixels	2 MP
	Video compression formats	H.264, H.264+, H.265, H.265+, M-JPEG
	Video streaming	Yes

Other images

