





Product Overview:

PWM air cooling solution with a stylish **Addressable RGB LED design**. Powered by Heat Core Touch Technology (HCTT) with **3 ultra-efficient thermal heat pipes**. **Top Down Cooling design** allows for more efficient heat dissipation. Black coating on fins increase heat dissipation area and improves efficiency of dissipation. Compatible with Addressable RGB motherboards or hubs (H66F).

Specifications

Model		Cylon 3
Base Material		Aluminum block with HCTT Heat Core Touch Technology
Fin Material		Aluminum
Heat pipe		Dia. 6mm x 3
Dimensions		126 x 138 x95mm
TDP(Thermal Design Power)		125
Fan	Speed	600-1800 rpm
	Connector	PWM 4-Pin
	Dimensions	120 x 120 x 25mm
	Bearing Type	Hydraulic Bearing
	Started Voltage	7V
	Rated Voltage	12V
	Rated Current	0.57 A
	Power Consumption	6.84 Watts
	Air Pressure	0.63-1.48 mm-H2O
	Air Flow	24.1-60.8 CFM
	Noise	13.3-24.3 dBA
	MTBF (Mean Time Before Failure)	60000 hrs.
Socket		LGA 115X/775 AM4/AM3+/AM3/AM2+/AM2/FM2/FM1

ALL TRADEMARKS ARE REGISTERED TO THEIR RESPECTIVE OWNERS.

Warranty

2 year

Features

1. Heat Core Touch Technology with 3 ultra-efficient thermal heat pipes
2. Built-in RGB LED lighting adds a stylish flair to your rig
3. Compatible with Addressable RGB motherboards (ASUS Aura Sync, MSI Mystic Light Sync, and Gigabyte RGB Fusion) or hubs (H66F)
4. Top Down Cooling design allows for more efficient heat dissipation and higher compatibility with cases
5. TDP (Thermal Design Power) up to 125W
6. Black coating on fins increases heat dissipation area and improves efficiency of dissipation
7. Upgraded high efficiency fins for maximum thermal performance
8. Compatible with most current motherboard designs

Package Information

Product Name	Product Number	EAN CODE	UPC CODE
Cylon 3 ARGB PWM 4P	ACTC-CL30310.71	4710562750225	

Carton Size (L x W x H)		Carton Weight	
Retail Box Size (L x W x H)		Retail Box Weight	
Carton Qty		Pallet Qty	

ALL TRADEMARKS ARE REGISTERED TO THEIR RESPECTIVE OWNERS.