GRAPHICS CARD GEFORCE® GTX 1660 SUPER™ AERO ITX OC







SPECIFICATION

Model Name	GeForce® GTX 1660 SUPER™ AERO ITX OC
Graphics Processing Unit	NVIDIA® GeForce® GTX 1660 SUPER™
Interface	PCI Express x16 3.0
Cores	1408 Units
Core Clocks	Boost: 1815 MHz
Memory Speed	14 Gbps
Memory	6GB GDDR6
Memory Bus	192-bit
Output	DL-DVI-D x 1 / DisplayPort x 1 (v1.4) / HDMI 2.0b x 1
HDCP Support	2.2
Power consumption	125 W
Power connectors	8-pin x 1
Recommended PSU	450 W
Card Dimension(mm)	179 x 127 x 42 mm
Weight (Card / Package)	561 g / 876 g
Afterburner OC	Y
DirectX Version Support	12 API
OpenGL Version Support	4.5
Maximum Displays	3
VR Ready	Y
G-SYNC® technology	Y
Digital Maximum Resolution	7680x4320

CONNECTIONS



1. DisplayPort
2. HDMI
3. DL-DVI-D

FEATURE

SMALL FORM FACTOR

MSI AERO ITX cards offer the power of a full size graphics card in an incredibly small package.

PERFECT IN ANY CASE

Thanks to a small form factor, MSI AERO ITX cards will fit into virtually any case.

MSI Afterburner

The ultimate overclocking software with advanced control options and real-time hardware monitor.

VR Ready

Certified to provide the performance required for a smooth experience in your VR adventures.

NVIDIA® G-SYNC®

Gives you more of what you want in a gaming experience. Incredibly smooth, tear-free gameplay at refresh rates up to 240 Hz.

Generated 2019-11-06, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

TRUE GAMING

© 2018 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved. © 2016 NVIDIA, the NVIDIA logo, GeForce, SHIELD, and NVIDIA G-SYNC are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries.