

WT6x Series Technical Accessory Guide

NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection.

** Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.*

Cradles/Charging

Part Number	Picture	Description	Notes	Required Items
CRD-NGWT-1S1BU-01		Single Slot Cradle	►Provides USB support ►Supports terminal and spare battery charging ►LED notification of spare battery charging status.	►Power Supply (PWR-BGA12V50W0WW and CBL-DC-388A1-01) ►AC Line Cord (23844-00-00R). ►Also requires Micro USB Cable (25-124330-01R) for host communication.
CRD1SLOT-WM-WT6000		Single Slot Cradle Kit	►Provides USB support ►Supports terminal and spare battery charging ►LED notification of spare battery charging status. ►Kit includes Single Slot Cradle (CRD-NGWT-1S1BU-01), Power Supply (PWR-BGA12V50W0WW), DC Line Cord (CBL-DC-388A1-01) and AC Line Cord (23844-00-00R). ►NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	►Requires Micro USB Cable (25-124330-01R) for host communication.
CRD1SLT-WM-WT6-INT		Single Slot Cradle Kit	►Provides USB support ►Supports terminal and spare battery charging ►LED notification of spare battery charging status. ►Kit includes Single Slot Cradle (CRD-NGWT-1S1BU-01), Power Supply (PWR-BGA12V50W0WW) and DC Line Cord (CBL-DC-388A1-01). ►NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	►AC Line Cord (23844-00-00R). ►Requires Micro USB Cable (25-124330-01R) for host communication.

CRD-NWTRS-2SUCH-01		Single Slot Cradle for WT6000 and RS6000	►Provides USB support to WT6000 and RS6000 ►Supports WT6000 and RS6000 ►Does not support spare battery charging ►LED notification of spare battery charging status.	►Power Supply (PWR-BGA12V50W0WW and CBL-DC-388A1-01) ►AC Line Cord (23844-00-00R). ►Also requires Micro USB Cable (25-124330-01R) for host communication.
CRD-NGWT-5S5BC-01		5-Slot Charge Only Cradle	►Charges 5 WT6000 units and 5 spare batteries ►Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01)	►DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW) ►AC Line Cord (23844-00-00R)
CRD5SLOT-WM-WT6000		5-Slot Charge Only Cradle Kit	►Charges 5 WT6000 units and 5 spare batteries ►Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). ►Kit includes 5-Slot Charge Only Cradle (CRD-NGWT-5S5BC-01), DC Line Cord (CBL-DC-382A1-01), Power Supply (PWR-BGA12V108W0WW) and AC Line Cord (23844-00-00R). ►NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	
CRD5SLT-WM-WT6-INT		5-Slot Charge Only Cradle Kit	►Charges 5 WT6000 units and 5 spare batteries ►Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). ►Kit includes 5-Slot Charge Only Cradle (CRD-NGWT-5S5BC-01), DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW). ►NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	►AC Line Cord (23844-00-00R)
CRD-NGWT-10SCH-01		10-Slot Charge Only Cradle	►Charges 10 WT6000 units ►Does not charge spare batteries ►Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01)	►DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW) ►AC Line Cord (23844-00-00R)
CRD-4WT6-4RS51-01		Multi-Slot Charge Only Cradle for WT6x and RS5100	►Charges 4 WT6x units, 4 WT6x Spare Batteries and 4 RS5100 units ►Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01).	►DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW) ►AC Line Cord (23844-00-00R)

CRD-NWTRS-10SCH-01		10-Slot Charge Only Cradle for WT6x and RS6x	►Charges 5 WT6x units and 5 RS6x units ►Does not charge spare batteries ►Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01)	►DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW) ►AC Line Cord (23844-00-00R)
CRD-10NW-GRD-01		10-Slot Charge Only Cradle for WT6x and RS6x Kit	►Charges 5 WT6x units and 5 RS6x units ►Does not charge spare batteries ►Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). ►Kit includes 10-Slot Charge Only Cradle for WT6x and RS6x(CRD-NWTRS-10SCH-01), Power Supply (PWR-BGA12V108W0WW), DC Line Cord (CBL-DC-382A1-01) and AC Line Cord (23844-00-00R). ►NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	
CRD-8NW-GRD-01		8-Slot Charge Only Cradle for WT6x, RS6x and Spare Batteries Kit	►Charges 4 WT6x units, 4 RS6x units and 4 Spare WT6x/RS6x Spare Batteries ►Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). ►Kit includes 8-Slot Charge Only Cradle for WT6x, RS6x and Spare Batteries (CRD-NWTRS-8SC4B-01), Power Supply (PWR-BGA12V108W0WW), DC Line Cord (CBL-DC-382A1-01) and AC Line Cord (23844-00-00R). ►NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	
SAC-HS3100-B8W8-01		8-Slot Charge Only Cradle for WT6000 and HS3100 batteries	►Charges 8 WT6000 units and 8 HS3100 Batteries ►Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01)	►DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW) ►AC Line Cord (23844-00-00R)
CRD-NGWT-5S5BE-01		5-Slot Ethernet + Charge Cradle	►Allows Ethernet speeds up to 1 Gb ►Charges 5 terminals and 5 spare batteries ►Can also be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01)	►DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW) ►AC Line Cord (23844-00-00R)
SAC-NWTRS-4SCH-01		4-Slot Battery Charger	►Charges up to 4 Spare Batteries ►Up to 4 Battery Chargers can be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01)	►Power Supply (PWR-BGA12V50W0WW and CBL-DC-388A1-01) ►AC Line Cord (23844-00-00R).

SACWT60-4-WM		4-Slot Battery Charger Kit with AC Line Cord	►Charges up to 4 Spare Batteries ►Up to 4 Battery Chargers can be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). ►Kit includes 4-Slot Battery Charger (SAC-NWTRS-4SCH-01), Power Supply (PWR-BGA12V50W0WW), DC Line Cord (CBL-DC-388A1-01) and AC Line Cord (23844-00-00R). ►NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	
SACWT60-4-WM-INT		4-Slot Battery Charger Kit	►Charges up to 4 Spare Batteries ►Up to 4 Battery Chargers can be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). ►Kit includes 4-Slot Battery Charger (SAC-NWTRS-4SCH-01), Power Supply (PWR-BGA12V50W0WW) and DC Line Cord (CBL-DC-388A1-01). ►NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	►AC Line Cord (23844-00-00R)
SAC-NWTRS-20SCH-01		20-Slot Battery Charger	►Charges up to 20 Spare Batteries ►Can be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01)	►DC Line Cord (CBL-DC-382A1-01) and Power Supply (PWR-BGA12V108W0WW) ►AC Line Cord (23844-00-00R)
SAC-20SLOT-GRD-01		20-Slot Battery Charger Kit	►Charges up to 20 Spare Batteries ►Can be wall or rack mounted using Mounting Bracket (BRKT-SCRD-SMRK-01). ►Kit includes 20-Slot Battery Charger (SAC-NWTRS-20SCH-01), DC Line Cord (CBL-DC-382A1-01), Power Supply (PWR-BGA12V108W0WW) and AC Line Cord (23844-00-00R). ►NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	
BRKT-SCRD-SMRK-01		Multi-Slot Wall/Rack Mount Bracket	►Allows for rack and wall mounting of one 5-Slot, 10-Slot, or 20-Slot Charger. Also can be used to mount up to four 4-Slot Battery Chargers or Single-Slot Cradles ►Bracket can be mounted on standard 19" network rack or on a wall. ►Cable routing slots & removable power supply holder tray. ►Adjustable tabs & screw mounts for easy hanging/installation. ►Adjustable orientations - horizontal, vertical, angled. ►See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket.	

Communication Cables

Part Number	Picture	Description	Notes	Required Items
25-124330-01R		USB Cradle to PC/Host cable	►Micro USB connection on cradle end	
CBL-NGWT-USBCHG-01		Snap-on USB Communication/Charging Cable	►Attaches to one of the accessory ports on WT6000	Power Supply (PWR-BUA5V16W0WW), DC Line Cord (CBL-DC-383A1-01) and AC Line Cord (50-16000-182R) for charging
CBL-NGWT-USBHD-01	 	/	►Connects to WT6000 to accessories with USB-C cable. ►Typically used with the**production version** of HD4000 Heads Up Display (HUD). ►Cable length is 80cm/approx 32 inches. ►Includes 2 aligator clips for attaching cable to clothing. ►See the HD4000 Technical Accessory Guide (TAG) for additional details.	
CBL-NGWT-USBH1-01		WT6000 to USB-A Adapter Cable	►Connects to WT6000 to accessories with USB-A connector (i.e. USB stick, keyboard, mice, etc.). ►Typically used with the**protoype version** of HD4000 Heads Up Display (HUD). ►See the HD4000 Technical Accessory Guide (TAG) for additional details. ►NOTE: This is a custom product. Please work with your Zebra representative to obtain Product Management approval if you would like to order this item.	
3rd party * (see http://www.cyberguys.com/product-details/?productid=33062)		USB micro-A to USB A Female adapter	►Allows the TC8000 to act as a USB host to connect to devices like USB flash drives/memory sticks, mice, etc. ►Connects to 2-Slot USB/Charge ShareCradle	

Soft Goods - Cases/Holsters

Part Number	Picture	Description	Notes	Required Items

SG-NGWT-WRMTS-02		Wrist Mount (Standard Strap)	►Uses BOA dial-to-fit design which is strong, durable, and easy to use. ►Velcro free design uses non-absorbent materials that can be wiped down. ►Includes Carrier, Comfort Pad (SG-NGWT-CMPD-02) and Small/Medium size Wrist Strap (SG-NGWT-WSTPST-01). ►White Dial and accent color on strap identify size as Standard (small/medium). ►Strap length can be adjusted between 128 to 191 mm (approx 5.0 to 7.5") ►It is typical for each user to have their own wrist mount (for hygiene). ►Improved design vs. SG-NGWT-WRMTS-01 uses updated Comfort Pad (SG-NGWT-CMPD-02) which now includes ridges in the top surface that assists with alignment during installation and reduces the occurrence of slippage, especially in the presence of sweat.	
SG-NGWT-WRMTS-01		Wrist Mount (Standard Strap)	►Discontinued 12/2018, now use SG-NGWT-WRMTS-02 - see PMB 10070. ►Uses BOA dial-to-fit design which is strong, durable, and easy to use. ►Velcro free design uses non-absorbent materials that can be wiped down. ►Includes Carrier, Comfort Pad (SG-NGWT-CMPD-01) and Small/Medium size Wrist Strap (SG-NGWT-WSTPST-01). ►White Dial and accent color on strap identify size as Standard (small/medium). ►Strap length can be adjusted between 128 to 191 mm (approx 5.0 to 7.5") ►It is typical for each user to have their own wrist mount (for hygiene).	
SG-NGWT-WRMTL-02		Wrist Mount (Extended Strap)	►Uses BOA dial-to-fit design which is strong, durable, and easy to use. ►Velcro free design uses non-absorbent materials that can be wiped down. ►Includes Carrier, Comfort Pad (SG-NGWT-CMPD-02) and Medium/Large size Wrist Strap (SG-NGWT-WSTPLN-01). ►Black Dial and accent color on strap identify size as Extended (medium/large). ►Strap length can be adjusted between 164 to 265 mm (approx 6.5 to 10.5") ►It is typical for each user to have their own wrist mount (for hygiene). ►Improved design vs. SG-NGWT-WRMTL-01 uses updated Comfort Pad (SG-NGWT-CMPD-02) which now includes ridges in the top surface that assists with alignment during installation and reduces the occurrence of slippage, especially in the presence of sweat.	


SG-NGWT-WRMTL-01	 	Wrist Mount (Extended Strap)	►Discontinued 12/2018, now use SG-NGWT-WRMTL-02 - see PMB 10070. ►Uses BOA dial-to-fit design which is strong, durable, and easy to use. ►Velcro free design uses non-absorbent materials that can be wiped down. ►Includes Carrier, Comfort Pad (SG-NGWT-CMPD-01) and Medium/Large size Wrist Strap (SG-NGWT-WSTPLN-01). ►Black Dial and accent color on strap identify size as Extended (medium/large). ►Strap length can be adjusted between 164 to 265 mm (approx 6.5 to 10.5") ►It is typical for each user to have their own wrist mount (for hygiene)	
SG-NGWT-WRMTXL-01		Wrist Mount (Extra Large Length Strap)	►Uses BOA dial-to-fit design which is strong, durable, and easy to use. ►Velcro free design uses non-absorbent materials that can be wiped down. ►Includes Carrier, Comfort Pad (SG-NGWT-CMPD-01) and Extra-Large size Wrist Strap (SG-NGWT-WSTPXL-01). ►Blue Dial and accent color on strap identify size as Extra-Large. ►Strap length is 375 mm (approx 14.75") ►This size strap is typically used in freezer environments where users may be wearing heavy jackets. ►It is typical for each user to have their own wrist mount (for hygiene).	
SG-NGWT-CMPD-02		Replacement Comfort Pad for wrist mount	►Soft Rubber ►Easily removable ►Hygienic ►Improved design vs. SG-NGWT-CMPD-01 which now includes ridges in the top surface that assists with alignment during installation and reduces the occurrence of slippage, especially in the presence of sweat.	
SG-NGWT-CMPD-01		Replacement Comfort Pad for wrist mount	►Soft Rubber ►Easily removable ►Hygienic	
SG-NGWT-WSTPST-01		Replacement Wrist Strap (standard size)	►White Dial and accent color on strap identify size as Standard (small/medium) ►Strap length can be adjusted between 128 to 191 mm (approx 5.0 to 7.5")	


SG-NGWT-WSTPLN-01		Replacement Wrist Strap (extended size)	►Black Dial and accent color on strap identify size as Extended (medium/large) ►Strap length can be adjusted between 164 to 265 mm (approx 6.5 to 10.5")	
SG-NGWT-WSTPXL-01		Replacement Wrist Strap (extra-large size)	►Blue Dial and accent color on strap identify size as extra-large. ►Strap length can be adjusted between 218 to 375 mm (approx 8.5 to 14.75")	
SG-WT4027050-01R		Arm Sleeve (pack of 5)	►Worn under WT6000 wrist mount if worker is in short-sleeved shirt and wants: - Extra sweat wicking/ personal layer - Extra comfort - Extra slip-resistance ►Material will not snag ►One size fits all ►Washable in mild detergent. Should be air dried. ►Pack of 5 Arm Sleeves	
(3rd party) * http://x.couver.us/extra-long-wristbands-pro-31/		Arm Sleeve	►Can be worn under WT6000 Wrist Mount in environments where excessive user sweat may cause the strap to slip ►Also can be worn by users that may have skin irritations from the wrist mount	

SG-NGWT-HPMNT-01		Hip-mount Clip	►Allows WT6000 to be worn on hip ►Will attach to clothing, user's belt, or optional Belt for Hip-mount Clip (11-08062-02R)	
SG-NGWT-HPMNT-02		Hip-mount Clip	►Allows WT6000 to be worn on hip ►Will attach to clothing, user's belt, or optional Belt for Hip-mount Clip (11-08062-02R). ►This Clip holds the WT6000 in the reverse orientation of SG-NGWT-HPMNT-01. ►NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	
(3rd party) * http://www.ultimacase.com		Additional holsters		
11-08062-02R		Belt for Hip-mount Clip	►Belt is 2 inches wide ►Extends to 48 inches ►Has improved buckle and softer belt material	
11-08062-01R		Belt for Hip-mount Clip	►Belt is 2 inches wide ►Extends to 48 inches ►Discontinued 9/2009, replaced by 11-08062-02R	
V6198DW (3rd party) * http://www.ultimacase.com		Belt Extender	►Used to extend the Hip-mount belt (11-08062-02R) an additional 10 inches	

Ring Scanner (RS5000) - 2D Imager


Part Number	Picture	Description	Notes	Required Items

RS5000-LCFSWR		RS5000 Ring Scanner with short cable (for wrist mount)	►Uses SE4710 scan engine. ►IP54 sealed ►Extended temperature spec down to -30C for freezer environments.	
RS5000-LCFLWR		RS5000 Ring Scanner with long cable (for hip mount)	►Uses SE4710 scan engine. ►IP54 sealed ►Extended temperature spec down to -30C for freezer environments.	
SG-NGRS-SFSVS-01R		RS5000 Spare Ring Scanner Strap (Short)	►Short finger strap - 6" long ►It is typical for each user to have their own ring scanner strap (for hygiene). ►This is the same strap that is included on each RS5000.	
SG-RS419-FGSTP-02R		RS4000/RS5000/ RS409/RS419 Spare Ring Scanner Strap (Long)	►Improvements include a new connection between the velcro and fabric used as part of the accessory. ►Long finger strap - 7.8" long ►It is typical for each user to have their own ring scanner strap (for hygiene).	
SG-NGRS-TRGASR-01R		RS5000 Replacement Trigger Assembly	►Uses same design as RS419 Trigger (SG-RS419-TRGAS-01R), but doesn't include laser warning label on trigger button.	
Ring Scanner (RS6000) - 2D Cordless Bluetooth Imager (see RS6000 Accessories document)				
Ring Scanner (RS4000) - 1D Laser				
Part Number	**Picture**	**Description**	**Notes**	**Required Items**
RS4000-HPCSWR		RS4000 Ring Scanner with short cable (for wrist mount)	►Uses SE965 scan engine with Adaptive Scanner for longer read ranges (near contact to 200 inches). ►Extended temperature spec down to -30C for freezer environments.	
RS4000-HPCLWR		RS4000 Ring Scanner with long cable (for hip mount)	►Uses SE965 scan engine with Adaptive Scanner for longer read ranges (near contact to 200 inches). ►Extended temperature spec down to -30C for freezer environments.	
SG-RS419-FGSTP-02R		RS4000/RS5000/ RS409/RS419 Spare Ring Scanner Strap (Long)	►Improvements include a new connection between the velcro and fabric used as part of the accessory. ►Long finger strap - 7.8" long ►It is typical for each user to have their own ring scanner strap (for hygiene). ►This is the same strap that is included on each RS419.	


SG-RS419-FGSTP-01R		RS4000/RS409/RS419 Spare Ring Scanner Strap (Long)	►Discontinued 7/2015, now use SG-RS419-FGSTP-02R - PMB 2670 ►Long finger strap - 7.8" long ►It is typical for each user to have their own ring scanner strap (for hygiene). ►Internal P/N - 21-162798-01 ►This is the same strap that is included on each RS419.	
21-93022-03R		RS4000/RS409/RS419 Spare Ring Scanner Strap (Short)	►Improvements include a new connection between the velcro and fabric used as part of the accessory. assemblyover previous version. ►Short finger strap - 6" long ►It is typical for each user to have their own ring scanner strap (for hygiene). ►This is the same strap that is included on each RS409.	
21-93022-02R		RS4000/RS409/RS419 Spare Ring Scanner Strap (Short)	►Discontinued 7/2015, now use 21-93022-03R - PMB 2670 ►Provides improvements in stitching and material strength over previous version. ►Short finger strap - 6" long ►It is typical for each user to have their own ring scanner strap (for hygiene). ►This is the same strap that is included on each RS409.	
SG-RS419-TRGAS-01R		RS4000/RS419 Replacement Trigger Assembly	Internal P/N - 21-156086-01	

Headset/Audio Accessories

Part Number	Picture	Description	Notes	Required Items
See HS2100-HS3100 Accessories Document		HS2100 Rugged Wired Headset	►Built to handle the everyday inevitable drops ►Dustproof, sprayproof and waterproof ►Ready for the freezer and outdoor subzero temperatures ►Feather-light for extraordinary comfort ►Noise cancellation for a superior voice experience in the noisiest environments ►Detachable swivel boom minimizes costs. ►Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. ►User-replaceable pads and windscreens maximize comfort and hygiene	Requires one of the following cable options: (1) HS2100 to WT6000 Cable (CBL-HS2100-12S1-01) OR (2) Quick Disconnect Headset cable (CBL-HS2100-QDC1-02) AND WT6000 to Quick Disconnect Adapter Cable (CBL-NGWT-AUQDST-02 or CBL-NGWT-AUQDLG-02) See HS2100/HS3100 Accessories Document for additional headset accessories
VR12 (3rd party) * http://www.blueparrott.com		BlueParrott VR12 Wired Noise Cancelling Headset	►Audio accuracy for voice picking and other speech recognition applications. ►High quality durability stands up to all-day, every-day use. ►Lightweight design is easy and comfortable to wear all day. ►Compatible with most major wearable computers and devices used in voice-picking environments. ►G type (GN Netcom) Quick Disconnect. ►Convertible design gives choice of over-the-head and behind-the-neck wearing styles	Quick Disconnect Headset to WT6000 Adapter Cable (CBL-NGWT-AUQDST-02 or CBL-NGWT-AUQDLG-02)

RCH51		RCH51 Rugged Cabled Headset	►Discontinued 12/2018, now use HS2100 series - PMB 2981 ►Improved to withstand chemicals in certain hair gels ►Noise cancelling microphone filters ambient noise inches away ►Extremely rugged strain relief features ensure cable bend tolerance, even at -30C ►IP67 sealing throughout the headset protects sensitive components from moisture and dust ►High-strength plastics survive 6' drop at -30C & 500 tumbles ►Weight: 4 oz. ►See RCH50/RCH51 Accessories Document for additional accessories	Quick Disconnect Headset to WT6000 Adapter Cable (CBL-NGWT-AUQDST-02 or CBL-NGWT-AUQDLG-02)
RCH50		RCH50 Rugged Cabled Headset	►Discontinued 10/2011, now use RCH51 ►Noise cancelling microphone filters ambient noise inches away ►Extremely rugged strain relief features ensure cable bend tolerance, even at -30C ►IP67 sealing throughout the headset protects sensitive components from moisture and dust ►High-strength plastics survive 6' drop at -30C & 500 tumbles ►Weight: 4 oz. ►See RCH50/RCH51 Accessories Document for additional accessories	Quick Disconnect Headset to WT6000 Adapter Cable (CBL-NGWT-AUQDST-02 or CBL-NGWT-AUQDLG-02)
3PTY-VXI-VR12 (Zebra orderable SKU) http://www.vxicorp.com		BlueParrot VR12 Wired Noise Cancelling Headset ZEBRA Compatible	►Discontinued 10/2018, now use HS2100 series - PMB 10005 ►Audio accuracy for voice picking and other speech recognition applications. ►High quality durability stands up to all-day, every-day use. ►Lightweight design is easy and comfortable to wear all day. ►Compatible with most major wearable computers and devices used in voice-picking environments. ►G type (GN Netcom) Quick Disconnect. ►Convertible design gives choice of over-the-head and behind-the-neck wearing styles	Quick Disconnect Headset to WT6000 Adapter Cable (CBL-NGWT-AUQDST-02 or CBL-NGWT-AUQDLG-02)

See HS2100-HS3100 Accessories Document		HS3100 Rugged Bluetooth Headset	►HD Voice, also known as Wide Band Audio, brings incredible audio clarity ►Built to handle the everyday inevitable drops ►Dustproof, sprayproof and waterproof ►Ready for the freezer and outdoor subzero temperatures ►Feather-light for extraordinary comfort ►Noise cancellation for a superior voice experience in the noisiest environments ►Swap batteries on the fly — without losing the Bluetooth connection ►Split-second tap-to-pair simplicity using NFC. ►Detachable swivel boom minimizes costs. ►Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. ►User-replaceable pads and windscreens maximize comfort and hygiene ►15 hours of battery power	See HS2100/HS3100 Accessories Document for headset accessories
various Bluetooth models B550-XT B350-XT C400-XT C300-XT (3rd party) * http://www.blueparrott.com		BlueParrott Bluetooth Headsets	►Various Bluetooth models available with options that include: - Blocking out 96% of background noise - Over 24 hours of talk time - NFC Tap to Pair capable - Bluetooth wireless range capable up to 300 ft. - Convertible wearing options: over the head, behind the neck. See BlueParrot site for model specific options.	
3PTY-VXI-B350XT (Zebra orderable SKU) http://www.vxicorp.com		BlueParrott Bluetooth Headset for voice directed applications ZEBRA Compatible	►Discontinued 10/2018, now use HS3100 series - PMB 10005 ►Used to enable Voice Directed Picking (VDP) or Speech Applications in warehouse environments when the use of a wireless headset is desired ►Not intended to support peer-to-peer communications (PTT) or VoIP calls. ►Provides 24 hours talk time. ►Allows the use of other BT devices (i.e. RS6000 scanner or mobile printer) ►Zebra Compatible certification for VDP application use with MC32.	
3PTY-VXI-B250XTP (Zebra orderable SKU) http://www.vxicorp.com		BlueParrott Bluetooth Headset for voice directed applications ZEBRA Compatible	►Discontinued 10/2018, now use HS3100 series - PMB 10005 ►Used to enable Voice Directed Picking (VDP) or Speech Applications in warehouse environments when the use of a wireless headset is desired ►Not intended to support peer-to-peer communications (PTT) or VoIP calls. ►Provides 20 hours talk time. ►Allows the use of other BT devices (i.e. RS6000 scanner or mobile printer)	

3PTY-VXI-EXPWAYII (Zebra orderable SKU) http://www.vxicorp.com		BlueParrott Bluetooth Headset for voice directed applications ZEBRA Compatible	►Discontinued 10/2018, now use HS3100 series - PMB 10005 ►Used to enable Voice Directed Picking (VDP) or Speech Applications in warehouse environments when the use of a wireless headset is desired ►Not intended to support peer-to-peer communications (PTT) or VoIP calls. ►Provides 8 hours talk time. ►Allows the use of other BT devices (i.e. RS6000 scanner or mobile printer) ►Zebra Compatible certification for VDP application use with MC92, VC70, WT41 and MC32.	
APTT1 (3rd party) * https://www.aina-wireless.com/	  	Aina Push-To-Talk (PTT) Bluetooth Voice Responder Remote Speaker/Mic (RSM)	►Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ►Includes clip for attaching device to closthing for lapel speaker/mic usage. ►Features several buttons which the application developers can assign to different functions. ►Users can remotely control functions such as push-to-talk, phone calls, channel switching and emergency alerts. ►Device is ruggedized, MIL-STD 810G and IP67. ►Long lasting battery designed for 24 hour approx battery life. Can be recharged via micro-USB port. ►Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private. ►Can be easily paired to mobile computer using NFC tap-to-pair.	
H3-B-1 (3rd party) * https://www.dellking.com	 	Wandfu H3 Push-To-Talk (PTT) Bluetooth Remote Speaker/Mic (RSM)	►Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ►Includes clip for attaching device to closthing for lapel speaker/mic usage. ►Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private.	

BTR-155 (3rd party) * K551011 (Zebra orderable SKU) ►Discontinued 3/2019, now order from Savox https://www.savoxaccessories.com	  	Savox BTR-155 Bluetooth Remote Speaker/Mic (RSM)	►Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ►Includes clip for attaching device to closthing for lapel speaker/mic usage. ►Rugged wireless speaker microphone IP55. ►Allows cable-free movement ►Familiar speaker microphone functions; PTT and volume buttons ►Includes 2.5mm headset jack allowing headphones to be connected for keeping conversations more private. ►LED status indication ►High speaker volume ►Includes: - Savox RSM - Modular Wired earpiece - Wall Charger - USB Cable - Quick Start Guide - Carrying Strap	
BTH-101 (3rd party) * https://www.savoxaccessories.com	 	Savox Push-To-Talk (PTT) Bluetooth Headset	►Bluetooth headset designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ►Also operates as standard Bluetooth headset for taking phone calls. ►Device is lightweight and ruggedized, IP55.	
CBL-HS2100-12S1-02		HS2100 Headset to WT6000 cable	►Connects HS2100 directly to WT6000 ►43" long straight cable ►Includes one clip for attaching to clothing. Additional clips can be purchased separately. ►Uses improved strain relief design vs. CBL-HS2100-12S1-01.	
CBL-HS2100-12S1-01		HS2100 Headset to WT6000 cable	►Connects HS2100 directly to WT6000 ►43" long straight cable ►Includes one clip for attaching to clothing. Additional clips can be purchased separately.	

CBL-NGWT-AUQDST-02		Headset Adapter Cable (short cable)	►Connects wired headsets with Quick Disconnect connector (i.e. HS2100/ RCH50/ RCH51, BlueParrot, Voxware, and Eartec headsets) to WT6000 ►Cable is used when WT6000 is worn on the wrist. ►Provides additional strength on Quick Disconnect connector vs. CBL-NGWT-AUQDST-01.	
CBL-NGWT-AUQDST-01		Headset Adapter Cable (short cable)	►Discontinued 3/2019, now use CBL-NGWT-AUQDST-02 - see PMB 10125. ►Connects wired headsets with Quick Disconnect connector (i.e. HS2100/ RCH50/ RCH51, BlueParrot, Voxware, and Eartec headsets) to WT6000 ►Cable is used when WT6000 is worn on the wrist	
CBL-NGWT-AUQDLG-02		Headset Adapter Cable (long cable)	►Connects wired headsets with Quick Disconnect connector (i.e.HS2100 / RCH50 RCH51, BlueParrot, Voxware, and Eartec headsets) to WT6000 ►Cable is used when WT6000 is worn on the hip. ►Provides additional strength on Quick Disconnect connector vs. CBL-NGWT-AUQDLG-01.	
CBL-NGWT-AUQDLG-01		Headset Adapter Cable (long cable)	►Discontinued 3/2019, now use CBL-NGWT-AUQDLG-02 - see PMB 10125. ►Connects wired headsets with Quick Disconnect connector (i.e.HS2100 / RCH50 RCH51, BlueParrot, Voxware, and Eartec headsets) to WT6000 ►Cable is used when WT6000 is worn on the hip	
25-129938-02R		Headset Training Y cable	►Connects two Quick Disconnect wired headsets to the WT6000 ►Extra cable to plug in a second headset or external speakers for training or performing a demo	

Misc

Part Number	Picture	Description	Notes	Required Items
KYPD-WT6XANFASM-01	 	Attachable Keyboard Kit	►Keyboard mimics WT4000 series 2-tap keyboard. ►Backlit keys. ►Powered from the WT6x. ►Attaches to the WT6x's right accessory port. ►Kit includes keyboard and Cleat (ACC WT6XCLTMNT-01) that attaches to rear of WT6X unit. ►Cleat includes corded scanner routing channel allowing the WT6000 and corded scanner to be worn on the left arm. ►Compatible with all WT6x cradles, soft goods and battery sizes.	
ACC-WT6XCLTMNT-01		Cleat for Attachable Keyboard	►Spare/replacement Cleat used with Attachable Keyboard. ►Typically included with Attachable Keyboard Kit (KYPD-WT6XANFASM-01). ►Includes screws for mounting to rear of WT6x.	

CBL-NGWT-HDVBAP-01		Vibrating Cable	►Connects to WT6000 and provides additional haptic feedback to user. ►Cable is normally attached to user's wrist ►Can be used in noisy environments o for hearing impaired users.	
MISC-WT6X-SCRN-01		Screen Protector (pack of 5)		

Power Cords/Power Supplies

Part Number	Picture	Description	Notes	Required Items
CBL-DC-388A1-01		DC Power Cord	►Used along with Power Supply PWR-BGA12V50W0WW to power Single Slot Cradle and 4-Slot Battery Charger. ►Cable length is 1.8 meters	
PWR-BGA12V50W0WW		Power Supply	►Used to power Single Slot Cradle and 4-Slot Battery Charger. ►100-240 VAC,12V, 4.16A, 50W ►Provides US DOE Level VI compliance for power efficiency. ►Replaces PWRS-14000-148R	DC Line Cord (CBL-DC-388A1-01) and AC Line Cord (23844-00-00R)
KIT-PWR-12V50W		Power Supply Kit	►Includes Power Supply (PWR-BGA12V50W0WW) and DC Line Cord (CBL-DC-388A1-01)	AC Line Cord (23844-00-00R)
PWRS-14000-148R		Power Supply with integrated DC Cord	►Discontinued 1/2017, now use PWR-BGA12V50W0WW and CBL-DC-388A1-01 - see PMB 2923 and PMB 2851 ►Replaces KT-14000-148R ►Used to power Single Slot Cradle and 4-Slot Battery Charger ►100-240 VAC,12VDC,3.33A ►Energy Star Compliant	23844-00-00R
50-14000-148R		Power Supply with integrated DC Cord	►Discontinued 12/2007 - replaced by KT-14000-148R ►Used to power Single Slot Cradle and 4-Slot Battery Charger	23844-00-00R
KT-14000-148R		Power Supply with integrated DC Cord	►Replaces 50-14000-148R ►Used to power Single Slot Cradle and 4-Slot Battery Charger ►Discontinued 12/2010 - now use PWRS-14000-148R	23844-00-00R

CBL-DC-383A1-01		DC Line Cord	►Used to power Snap-On USB/Charge Cable with Power Supply PWR-BUA5V16W0WW ►Cable length is 6 ft.	
PWR-BUA5V16W0WW		Power Supply	►Used with Snap-On USB/Charge Cable ►100-240VAC, 5.4V, 3A, 16W ►Meets US DOE Level VI efficiency standard ►Replaces PWRS-14000-249R	DC Line Cord (CBL-DC-383A1-01) and AC Line Cord (50-16000-182R)
PWRS-14000-249R		Power Supply with integrated DC Cord	►Discontinued 10/2016 in NALA and 1/2017 in EMEA/APAC - replaced by PWR-BUA5V16W0WW and CBL-DC-383A1-01 - PMB 2887. ►Replaces 50-14000-249R ►Used with Snap-On USB/Charge Cable ►100-240VAC,5.4 VDC,3A ►Energy Star Compliant	50-16000-182R
50-14000-147R		Power Supply with integrated DC Cord	►Discontinued 12/2007 - replaced by 50-14000-249R ►Used with Snap-On USB/Charge Cable	50-16000-182R
50-14000-249R		Power Supply with integrated DC Cord	►Replaces 50-14000-147R ►Used with Communication/Charge Cable Cups ►Used with Snap-On USB/Charge Cable	50-16000-182R
CBL-DC-381A1-01		DC Power Cord	►Used to power 5-Slot ShareCradles when using Level VI Efficiency power supply (PWR-BGA12V108W0WW) ►This cable does not include the black extension release latch which is not required when used on Multi-Slot ShareCradles. ►CBL-DC-382A1-01 is still typically used though.	
CBL-DC-382A1-01		DC Power Cord	►Used with Power Supply PWR-BGA12V108W0WW to power 5-Slot, 10-Slot, 20-Slot Cradles	
50-16002-029R		DC Power Cord	►Used with Power Supply PWRS-14000-241R to power 5-Slot, 10-Slot, 20-Slot Cradles ►Discontinued 2/2017, now use CBL-DC-382A1-01 - PMB 2851 and 2933	

PWR-BGA12V108W0WW		Power Supply	►Used to power 5-Slot, 10-Slot, 20-Slot Cradles ►100-240 VAC, 12V, 9A, 108W ►Provides US DOE Level VI compliance for power efficiency. ►Replaces PWRS-14000-241R	CBL-DC-382A1-01 and 23844-00-00R
PWRS-14000-241R		Power Supply	►Replaces 50-14000-241R ►Used to power 5-Slot, 10-Slot, 20-Slot Cradles ►100-240VAC,12VDC,9A ►Energy Star Compliant ►Discontinued 2/2017, now use PWR-BGA12V108W0WW - PMB 2851 and 2933	50-16002-029R and 23844-00-00R
50-14001-004R		Power Supply	►Discontinued 12/2007 - replaced by 50-14000-241R ►Used to power 5-Slot, 10-Slot, 20-Slot Cradles	50-16002-029R and 23844-00-00R
50-14000-241R		Power Supply	►Replaces 50-14001-004R ►Used to power 5-Slot, 10-Slot, 20-Slot Cradles ►Discontinued 12/2010 - now use PWRS-14000-241R	50-16002-029R and 23844-00-00R
23844-00-00R		AC Line Cord	►Used to power all cradles. ►This AC Line Cord is for use in North America. See the **AC Line Cords by Country** TAG for comparable line cords to use in other countries.	
50-16000-182R		AC Line Cord	►Used with PWR-BUA5V16W0WW to power Snap-on charging cables. ►This AC Line Cord is for use in North America. See the **AC Line Cords by Country** TAG for comparable line cords to use in other countries.	

Batteries

Part Number	Picture	Description	Notes	Required Items
BTRY-NWTRS-33MA-02 BTRY-NWTRS-33MA-IN (for use in India)		Spare Standard Capacity Battery with PowerPrecision+ (3350 mAh)	►Has improved battery latching mechanism vs. BTRY-NWTRS-33MA-01 ►Designed, manufactured & tested to meet rigorous controls & standards ►Premium-grade cells with higher capacity & longer life cycle ►Designed to help prevent overcharging & electrical shock ►Strong & robust housing for optimal performance & durability ►Information available: - Available charge status - Total charge accumulated on the battery - Basic state of health ►Compatible with WT6000 and RS6000	

BTRY-NWTRS-33MA-01		Spare Standard Capacity Battery with PowerPrecision+ (3350 mAh)	►Discontinued 3/2018, now use BTRY-NWTRS-33MA-02, PMB 3115 ►Designed, manufactured & tested to meet rigorous controls & standards ►Premium-grade cells with higher capacity & longer life cycle ►Designed to help prevent overcharging & electrical shock ►Strong & robust housing for optimal performance & durability ►Information available: - Available charge status - Total charge accumulated on the battery - Basic state of health ►Compatible with WT6000 and RS6000	
BTRY-NGWT-50MA-01 BTRY-NGWT-50MA-IN (for use in India)		Spare Extended Capacity Battery with PowerPrecision+ (5000 mAh)	►Provides 50% more battery capacity than Standard Capacity Battery. ►Provides operating temperature spec down to -30°C, for cold chain and freezer use cases. ►Designed, manufactured & tested to meet rigorous controls & standards ►Premium-grade cells with higher capacity & longer life cycle ►Designed to help prevent overcharging & electrical shock ►Strong & robust housing for optimal performance & durability ►Information available: - Available charge status - Total charge accumulated on the battery - Basic state of health ►Only compatible with WT6000. Not compatible with RS6000 Ring Scanner. ►When charging while in WT6000, device must be inserted into cradle via cradle contacts on left side of device.	