THERMAL PRINTER



www.nilox.com

Model: NX-P382-USL

Thermal Printer NX-P382-USL

Our new printer ready for every field has the latest technology in thermal printing. Functional, adaptable to any area.
High speed impresion (250mm/s) that will satisfy all customers needs.
Satisfaction guaranteed with the new NX-P382-USL

Characteristics

- 250mm/s high printing speed, easy maintenance
- Noiseless, images printing at high speed.
- Paper easily rechargeable, with self-cutter with partial or full option.
- End of paper warning
- Error warning
- Flexible installation (wall support included in printer's base)
- ESC/POS emulation
- Works with Windows 2000 / XP / Vista / 7 / 8 / 8.1 / 10 / Linux / iOS / MacOS
- Interface USB + RS-232 + Ethernet
- Option of USB configuration like virtual COM
- Supports driver OPOS



SPECIFICATIONS

Model	NX-P382-USL
Printing method	Thermal
Printing Speed	250mm/s
Resolution	8 dots/mm, 203 dots/line
Characters	ANK, GB18030 (Chinese)
Print source	ANK: 12 x 24,9 x 17, Chinese: 24 x 24
Characters per line	48-Source A / 64-Source B
Paper type	Thermal paper
Paper size	79.5±0.5mm
Paper roll diameter	Max: 80.0mm
Inner paper roll diameter	13mm (minimum)
Paper thickness	0.06 to 0.07mm
Paper loading method	Load (Drop-in)
MCBF	60 milion lines
Cutter life	1.000.000 cuts
Head life	100 km
Barcode	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93, CODE128
Emulation	ESC/POS
Driver	Windows 2000 / XP / Vista / 7 / 8 / 8.1 / 10 / Linux / iOS / Android / MacOS
Sensor	End of paper proximity and End of paper
Cash drawer port	1 port RJ-11
Interface	USB + RS-232 + Ethernet
Power source	Ac100 ~ 240V (± 10%) DC 24V, 2.5A
Net weight	1.3kg
Gross weight	2.8kg
Dimensions (Printer)	198 x 140 x 130 mm
Complements	USB and RS-232 connection cables
Environmental parameters	Operative temp. -20ºC - 70º / Operative humidity 20% - 85%

The manufacturer reserves the right to modify the speceifactions without prior notice



Wall stand
included in the base



Nilox- Property of Esprinet S.p.A.
Via Energy Park 20
20871 Vimercate (MB) - Italy
Web: www.nilox.com