

DisplayPort to VGA Converter

No.: 38316

Connects a DisplayPort source to a VGA monitor

Description

- Connects a DisplayPort source to a VGA display or projector
- Supports resolutions up to 1920x1080@60Hz
- Can be used to add a secondary display for extended or mirrored desktop
- Active chipset for enhanced compatibility with graphics cards
- 2 year warranty

Active DisplayPort to VGA video converters are low cost, hassle free solutions for converting DisplayPort video signals to a VGA video output and connecting an additional display for an enhanced multi-screen experience.

The Lindy DisplayPort to VGA Converter connects a DisplayPort equipped source such as a PC or laptop to a VGA monitor. It supports high definition video resolutions up to 1920x1080@60Hz. Active conversion technology ensures compatibility with various graphics cards including AMD Eyefinity, NVIDIA surround and Intel Collage.

This converter can also be used to extend or mirror the desktop display to increase productivity in the workplace or home. Internal copper shielding provides enhanced reliability and compatibility. Due to its compact size and lightweight form factor the converter makes the perfect travel accessory for use with laptops, notebooks and ultrabooks to connect to VGA displays or projectors, perfect for BYOD work environments. The converter supports plug and play installation ensuring hassle-free setup.

Technical details

Specifications

- AV Interface: DisplayPort to VGA
- Interface Standard: DisplayPort 1.1 / VGA
- Supported Bandwidth: 180MHz
- Maximum Input Resolution: 1920x1080@60Hz
- Maximum Output Resolution: 1920x1080@60Hz
- Chipset: ANX9833
- HDCP Support: -
- Supported Audio: -
- Separate Audio Ports: -
- Special Features: -

Connectors

- Input: DisplayPort (Male)
- Output: VGA (Female)

Physical properties

- Dimensions (approx.) WxDxH:
  - 41.8x38x15.4mm (1.65x1.5x0.61in)
  - 34x19.8x11mm (1.34x0.74x0.43in) / DP
- Cable Length: 100mm (3.94in)
- Housing Material: ABS
- Jacket Material: PVC
- Jacket Diameter: 4.5mm (0.18in)
- Minimum Bend Radius: 45mm (1.77in)
- Net Weight: 0.045kg (0.1lb)
- Operating Temperature: 0° to 70° (32°F - 158°F)
- Storage Temperature: -10° to +80° (14°F - 176°F)
- Humidity: 5 - 90% RH (non-condensing)
- Colour: Black

Miscellaneous

- Packaging Type: Polybag
- Packaging Dimensions: 176x194x20mm (6.93x7.64x0.79in)
- Gross Weight: 0.049kg (0.11lb)
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH, Calif. Prop. 65

Package Contents

- DisplayPort to VGA Converter

Purchasing Information

- No.: 38316
- EAN: 4002888383165

© LINDY 2019