GRAPHICS CARD

GeForce RTX 2080 SUPER™ VENTUS XS








SPECIFICATION

Model Name	GeForce® RTX 2080 SUPER™ VENTUS XS
Graphics Processing Unit	NVIDIA® GeForce® RTX 2080 SUPER™
Interface	PCI Express x16 3.0
Cores	3072 Units
Core Clocks	Boost:1815 MHz
Memory Speed	15.5 Gpbs
Memory	8GB GDDR6
Memory Bus	256-bit
Output	DisplayPort x 3 (v1.4) / HDMI 2.0b x 1
HDCP Support	2.2
Power consumption	250 W
Power connectors	6-pin x 1 / 8-pin x 1
Recommended PSU	650 W
Card Dimension(mm)	257 x 127 x 51mm
Weight (Card / Package)	962 g / 1447 g
DirectX Version Support	12 API
OpenGL Version Support	4.5
Multi-GPU Technology	NVIDIA® NVLINK™ (SLI-Ready), 2-way
Maximum Displays	4
VR Ready	Y
G-SYNC® technology	Y
Adaptive Vertical Sync	Y
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



1. DisplayPort
2. HDMI

FEATURE

DUAL FAN THERMAL DESIGN

Dual fans covers more area of heatsink to take heat away more efficiently.

TORX FAN 2.0

Award-winning fan design combining two different fin designs for cool & quiet gaming.

SOLID BACKPLATE

Increases toughness of the card to prevent bending while complementing the design.

MSI Afterburner

The ultimate overclocking software with advanced control options and real-time hardware monitor.

VR Ready

Certified to provide the performance required for a smooth experience in your VR adventures.

NVIDIA® G-SYNC®

Gives you more of what you want in a gaming experience. Incredibly smooth, tear-free gameplay at refresh rates up to 240 Hz.

Generated 2019-12-23, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

TRUE GAMING

© 2018 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved. © 2016 NVIDIA, the NVIDIA logo, GeForce, SHIELD, and NVIDIA G-SYNC are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries.