LKexv 2600

MediLine



Gross/net capacity	240/221 litre
Ext. dimensions in mm (w/d/h)	600/610/1250
Int. dimensions in mm (w/d/h)	470/440/1062
Energy consumption in 365 days	287 kWh
Climate rating	5 [1]
Refrigerant	R 600a
Airborne acoustical noise emissions	48 dB(A)
Connection Rating	1.0 A
Voltage	220-240 V~
Cooling system	forced-air
Defrosting	automatic
Temperature range	+1°C to +15°C
Gradient *	6.4°C
Max. fluctuation **	5.5°C
Housing material/colour	steel/white
Door/lid material	Steel
Liner Material	moulded polystyrol white
Type of Control	analgoue controls
Temperature display	außen digital
Adjustable Shelving	4
Shelf material	glass
Shelf loading	40 kg
Handle	Ergonomic door handle
Lock	fitted
Door hinges	right, reversible
Gross/net weight	53 / 49 kg
EAN-Nr.	9005382164891

Subject to modification. Timestamp: 20.06.2018

1 **Climate class** / Climate Rating: **SN** +10°C to +32°C **N** +16°C to +32°C **ST** +16°C to +38°C **T** +16°C to +43°C
3 +10°C to +25°C **4** +10°C to +30°C **5** +10°C to +40°C **7** +10°C to +35°C

* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

LIEBHERR