

0.5m DisplayPort Extension Cable

No.: 41622

DP Male to Female

Description

- Professional choice DisplayPort 1.2 cable for commercial and high performance AV and IT installations
- Supports resolutions up to 4K 60Hz, 4096 x 2160
- Robust ABS housing 24K gold plated connectors and contacts
- Triple shielded cable, corrosion resistant tinned copper 28AWG conductors
- DisplayPort 1.2, 21.6Gbps; 10 year warranty

DisplayPort Extension cable with triple shielded 28AWG tinned copper conductors for performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

DisplayPort Extension cables are available in lengths from 0.5m to 3m.

Technical details

Connectors

- Connector A: DisplayPort Male
- Connector B: DisplayPort Female
- Housing Material: PVC + ABS
- Connector Plating: Gold plated
- Pin Construction: Copper
- Pin Plating: Gold plated
- Dimensions (approx.) WxDxH:
  - M: 20x45x11mm (0.79x1.77x0.43in)
  - F: 21.8x38.8x11.5mm (0.86x1.53x0.45in)

Cable Construction

- Length: 0.5m (1.64ft)
- Standard: DP 1.2
- Colour: Black
- Type: Round
- Jacket Diameter: 6.5mm (0.27in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 28AWG
- Shielding: Copper Braid 85%

Specifications

- Supported Bandwidth: 21.6 Gbps

- Maximum Resolution: 4K@60Hz
- Nominal Attenuation: -5dB@100MHz-450MHz, -37.1dB@ 450MHz-7GHz
- Minimum Band Radius: 65mm (2.56in)
- Operating Temperature: 0°C - 45°C (-17.8°F - 113°F)
- Storage Temperature: -10°C - 70°C (14°F - 158°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 10
- Certificated: RoHS, REACH, UL

Purchasing Information

- No.: 41622
- EAN: 4002888416221

This product is also available in other lengths

- 41622 - 0.5m (1.64ft)
- 41623 - 1m (3.28ft)
- 41624 - 2m (6.56ft)
- 41625 - 3m (9.84ft)

© LINDY 2020