

Ledinaire floodlight

BVP154 LED10/830 PSU 10W VWB CE

LED Module 1000 lm - 830 warm white - Power supply unit - Very wide beam angle 100°

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires that come with the Philips high-quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

Product data

General Information	
Lamp family code	LED10 [LED Module 1000 lm]
Light source colour	830 warm white
Light source replaceable	No
Number of gear units	-
Driver/power unit/transformer	PSU [Power supply unit]
Driver included	Yes
Optical cover/lens type	GC [Clear glass]
Luminaire light beam spread	100°
Control interface	-
Connection	Flying leads/cables
Cable	Cable 1.0 m without plug (C1K)
Protection class IEC	Safety class I
Flammability mark	NO [-]
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Outdoor optic type	Very wide beam angle 100°
Constant light output	No
Number of products on MCB	220

LED engine type	LED
Light Technical	
Upward light output ratio	0
Standard tilt angle post-top	0°
Standard tilt angle side entry	0°
Operating and Electrical	
Input voltage	220 to 240 V
Input frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
End CLO power consumption	- W
Inrush current	0.54 A
Inrush time	0.0054 ms
Power factor (min.)	0.9
Controls and Dimming	
Dimmable	No

Ledinaire floodlight

Mechanical and Housing	
Housing material	Aluminium die–cast
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Glass
Fixation material	Steel
Mounting device	MBA [Mounting bracket adjustable]
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	96 mm
Overall width	31 mm
Overall height	137 mm
Effective projected area	0.01 m²
Colour	Aluminium and Grey
Dimensions (height x width x depth)	137 x 31 x 96 mm (5.4 x 1.2 x 3.8 in)

Approval and Application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Surge protection (common/differential)	Surge protection level until 2 kV

Initial Performance (IEC Compliant)	
Initial luminous flux	1000 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Init. Corr. colour temperature	3000 K
Init. colour rendering index	80
Initial chromaticity	<7 SDCM
Initial input power	10 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50,000 h	10 %
Useful life L80B10	32000 h
Lumen maintenance at median useful life* 50,000 h	L70

Application Conditions	
Ambient temperature range	-25 to +40 °C
Maximum dimming level	Not applicable

Product Data	
Full product code	871016332970399
Order product name	BVP154 LED10/830 PSU 10W VWB CE
EAN/UPC – product	8710163329703
Order code	32970399
Numerator – quantity per pack	1
Numerator – packs per outer box	18
Material no. (12NC)	911401730422
Net weight (piece)	0.350 kg



Dimensional drawing



Ledinaire floodlight BVP105/106



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com
2020, January 16 - data subject to change