

Ledinaire Batten

BN013C LED10S/830 L600

830 warm white

The Ledinaire range contains a selection of popular off-the-shelf LED luminaires that comes with high Philips quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need. Both integrated (BN012C) and TLED-based (BN060C) versions are available

Product data

General Information	
Beam angle of light source	- °
Light source colour	830 warm white
Cap base	G13 [Medium Bi-Pin Fluorescent]
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	PSU [Power supply unit]
Driver included	Yes
Optic type	VWB [Very wide beam]
Luminaire light beam spread	154°
Control interface	-
Connection	Push-in connector 2-pole
Cable	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	F [For mounting on normally flammable surfaces]
CE mark	CE mark
ENEC mark	-
Warranty period	5 years
Constant light output	No

Number of products on MCB	10
Unified glare rating CEN	26

Operating and Electrical	
Input voltage	220 to 240 V
Input frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	- W
Inrush current	3.92 A
Inrush time	0.043 ms
Power factor (min.)	0.9

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Housing material	Polycarbonate
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate

Ledinaire Batten

Fixation material	-
Optical cover/lens finish	Opal
Overall length	612 mm
Overall width	30 mm
Overall height	36.5 mm
Colour	White
Dimensions (height x width x depth)	37 x 30 x 612 mm (1.4 x 1.2 x 24.1 in)

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]

Initial Performance (IEC Compliant)

Initial luminous flux	940 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	100 lm/W
Init. Corr. colour temperature	3000 K
Init. colour rendering index	≥80
Initial chromaticity	0.4282, 0.3979, SDCM≤5
Initial input power	10 W
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50,000 h	7.50 %
Lumen maintenance at median useful life* 50,000 h	L65

Application Conditions

Ambient temperature range	-20 to +35 °C
Performance ambient temperature Tq	25 °C
Maximum dimming level	Not applicable
Suitable for random switching	Not applicable

Product Data

Full product code	871016334955899
Order product name	BN013C LED10S/830 L600
EAN/UPC – product	8710163349558
Order code	34955899
Numerator – quantity per pack	1
Numerator – packs per outer box	25
Material no. (12NC)	911401836080
Net weight (piece)	0.150 kg



Dimensional drawing



Batten BN060C



© 2020 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com
2020, January 17 - data subject to change