AEG

120 cm Ceiling

DCE5260HM



Designed for space
Installed in the ceiling above your kitchen island, this attractive cooker hood not only cleans the kitchen air, it maintains the sleek finish of streamlined open-plan spaces.

Installed in the ceiling above your kitchen island, this attractive cooker hood not only cleans the kitchen air, it maintains the sleek finish of streamlined open-plan spaces.

Product Benefits & Features



The hands-free hood
This cooker hood has Hob2Hood, a useful feature that automatically controls your cooker hood and lights. Leave Hob2Hood to regulate the fan while you concentrate on the key moments involved in getting your dish just right. But if you'd rather adjust the fan speed yourself, there are manual controls on the cooker hood too.



Clean air with less energy
A strong motor with low-energy consumption means this hood is reliable and efficienty clears away kitchen odours.



Clean air. Faster.
This Cooker hood clears the kitchen from cooking fumes quickly. That is beacuse the advanced cooker hood has an effecient and powerful motor.

Benefit from long-lasting lighting
Gain the benefits of LED lighting. Clear and bright, it makes ideal task lighting over a hob and, additionally, it's long-lasting and energy-efficient too.

REGULATE COOKING. REMOTELY
Set the optimal conditions for cooking with the hood's remote control. It enables quick, convenient adjustments from anywhere in the kitchen. So there's one less distraction when it comes to finessing flavor.

- Electronic variable 3+Intensive speed push button control
- Washable aluminium grease filters
- Extraction mode
- Maximum recirculation rate of 290 m³/h
- 61 dB(A) noise level
- Recirculation or extraction options

AEG

120 cm Ceiling
DCE5260HM

Product Specification

Installation	Ceiling
Size	120
Dimensions, HxWxD	382-582x1200x700
Minimum distance from cooking top	75
Minimum distance from cooking top	75
Cord Length	1.4
Voltage	230-240
Required Fuse	No
Frequency	50
Colour	Stainless steel
Superperforming charcoal filter compatible	MCFB62, 902 980 207
Energy class	A
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filter efficiency class	D
Capacity minimum, m3/h	315
Capacity, Max m³/h	590
Capacity intensive, m3/h	710
Sound power min speed, dB(A)	54
Sound power max speed, dB(A)	63
Sound power intensive, dB(A)	67
No. of speed settings	3+Intensive
Lamp type	Dimmable LED stripe
No. of lamps	1

Grease filters	6
Recirc sound power min, dB(A)	56
Recirc sound power max, dB(A)	68
Recirculation min, m3/h	300
Recirculation max, m3/h	580
Recirculation intensive, m3/h	690

