Sliding 70 cm Chimney Hood

DBE5761HG



Clean lines, clean air
Powered by an energy-efficient motor, this well-designed chimney hood is installed against the wall, effectively reduces kitchen odours while adding to the look and feel of the space itself.

Powered by an energy-efficient motor, this well-designed chimney hood is installed against the wall, effectively reduces kitchen odours while adding to the look and feel of the space itself.

Product Benefits & Features



The hands-free hood
This cooker hood has Hob2Hood, a useful feature that automatically controls your cooker hood and lights. Leave Hob2Hood to regulate the fan while you concentrate on the key moments involved in getting your dish just right. But if you'd rather adjust the fan speed yourself, there are manual controls on the cooker hood too.



Natural air, effortlessly and silently.
The sleekly designed AEG hood removes lingering odours quietly thanks to a super quiet breeze technology. So you can have a better environment in your kitchen effortlessly and silently.



Benefit from long-lasting lighting
Gain the benefits of LED lighting. Clear and bright, it makes ideal task lighting over a hob and, additionally, it's long-lasting and energy-efficient too.

Clean air with less energy
A strong motor with low-energy consumption means this hood is reliable and efficienty clears away kitchen odours.

All cooking vapours removed – in silence
Thanks to innovative technology, this hood clears your kitchen of unwanted cooking vapours almost unnoticably. What's more, the cooker hood's virtually silent operation helps you create the perfect atmosphere in your home.

- Washable aluminium grease filters
- Extraction mode
- Maximum recirculation rate of 220 m³/h
- 65 dB(A) noise level
- Recirculation or extraction options
- For wall mounting between furniture or as a stand alone unit

AEG

Sliding 70 cm Chimney Hood

DBE5761HG

Product Specification

Installation	Chimney
Size	70
Dimensions, HxWxD	759-1204x700x455
Minimum distance from cooking top	50
Minimum distance from cooking top	65
Cord Length	1.3
Voltage	220-240
Required Fuse	No
Frequency	50
Colour	Stainless steel
Charcoal filter type	MCFB58
Superperforming charcoal filter compatible	MCFB66, 902 980 215
Energy class	A
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filter efficiency class	B
Capacity minimum, m3/h	285
Capacity, Max m³/h	400
Capacity intensive, m3/h	700
Sound power min speed, dB(A)	44
Sound power max speed, dB(A)	54
Sound power intensive, dB(A)	65
No. of speed settings	3+Intensive, Breeze function
Lamp type	LED spotlight

No. of lamps	2
Grease filters	2
Recirc sound power min, dB(A)	55
Recirc sound power max, dB(A)	66
Recirculation min, m3/h	250
Recirculation max, m3/h	380